



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>5</sup> :</b> <b>A61K 7/06, 7/08, 7/48</b>		<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 92/16187</b>
			<b>(43) International Publication Date:</b> 1 October 1992 (01.10.92)
<b>(21) International Application Number:</b> PCT/US92/00805 <b>(22) International Filing Date:</b> 31 January 1992 (31.01.92) <b>(30) Priority data:</b> 671,576 19 March 1991 (19.03.91) US 776,960 15 October 1991 (15.10.91) US <b>(71) Applicant:</b> THE PROCTER & GAMBLE COMPANY [US/US]; One Procter & Gamble Plaza, Cincinnati, OH 45202 (US). <b>(72) Inventors:</b> COFFINDAFFER, Timothy, Woodrow ; 118 Bridle Lane, Loveland, OH 45140 (US). MONICH, Melissa, Smith ; 10574 Latina Ct., Cincinnati, OH 45218 (US). LEITCH, Steven, Hilary ; 2840-E Macintosh Lane, Maineville, OH 45039 (US). McCALL, Patrick, Columkille ; 10736 Bridle Path Lane, Cincinnati, OH 45215 (US).			<b>(74) Agent:</b> REED, T., David; The Procter & Gamble Company, Ivorydale Technical Ctr., 5299 Spring Grove Ave., Cincinnati, OH 45217-1087 (US). <b>(81) Designated States:</b> AT, AT (European patent), AU, BB, BE (European patent), BF (OAPI patent), BG, BJ (OAPI patent), BR, CA, CF (OAPI patent), CG (OAPI patent), CH, CH (European patent), CI (OAPI patent), CM (OAPI patent), CS, DE, DE (European patent), DK, DK (European patent), ES, ES (European patent), FI, FR (European patent), GA (OAPI patent), GB, GB (European patent), GN (OAPI patent), GR (European patent), HU, IT (European patent), JP, KP, KR, LK, LU, LU (European patent), MC (European patent), MG, ML (OAPI patent), MN, MR (OAPI patent), MW, NL, NL (European patent), NO, PL, RO, RU, SD, SE, SE (European patent), SN (OAPI patent), TD (OAPI patent), TG (OAPI patent). <b>Published</b> <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>
<b>(54) Title:</b> COSMETIC COMPOSITIONS CONTAINING HYDROPHOBICALLY MODIFIED NONIONIC POLYMER AND UNSATURATED QUATERNARY AMMONIUM SURFACTANT			
<b>(57) Abstract</b> <p>Disclosed is a vehicle system having a thickening system which comprises a nonionic long-chain alkylated water-soluble polymer and a specific cationic quaternary ammonium surfactant component dispersed in a compatible solvent. The quaternary surfactant component has an iodine value of at least about 15. The quaternary surfactant component is characterized by having a sufficient level of unsaturated C<sub>14</sub>-C<sub>22</sub> alkyl or C<sub>14</sub>-C<sub>22</sub> alkyl amido C<sub>2</sub>-C<sub>6</sub> alkylene radicals such that the average iodine value is at least about 15. These vehicle systems are useful in cosmetic compositions which are used to deliver an active component to the hair or skin. The vehicle systems are particularly useful in hair care compositions, especially rinse-off hair conditioning and styling compositions. In a particular rinse-off hair styling and conditioning composition hereof, the composition contains a vehicle system, as described above, and additionally contains a hair setting agent, a distributing aid, and a mono-long chain, tri-short chain quaternary ammonium surfactant.</p>			

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FI	Finland	MI	Mali
AU	Australia	FR	France	MN	Mongolia
BB	Barbados	GA	Gabon	MR	Mauritania
BE	Belgium	GB	United Kingdom	MW	Malawi
BF	Burkina Faso	GN	Guinea	NL	Netherlands
BG	Bulgaria	GR	Greece	NO	Norway
BJ	Benin	HU	Hungary	PL	Poland
BR	Brazil	IE	Ireland	RO	Romania
CA	Canada	IT	Italy	RU	Russian Federation
CF	Central African Republic	JP	Japan	SD	Sudan
CG	Congo	KP	Democratic People's Republic of Korea	SE	Sweden
CH	Switzerland			SN	Senegal
CI	Côte d'Ivoire	KR	Republic of Korea	SU	Soviet Union
CM	Cameroon	LI	Liechtenstein	TD	Chad
CS	Czechoslovakia	LK	Sri Lanka	TG	Togo
DE	Germany	LU	Luxembourg	US	United States of America
DK	Denmark	MC	Monaco		
ES	Spain	MG	Madagascar		

**COSMETIC COMPOSITIONS CONTAINING HYDROPHOBICALLY  
MODIFIED NONIONIC POLYMER AND UNSATURATED  
QUATERNARY AMMONIUM SURFACTANT**

5

**TECHNICAL FIELD**

10       The present invention relates to novel vehicle systems, and  
cosmetic compositions formulated therewith, based on nonionic long  
chain alkylated water-soluble polymer derivatives and unsaturated  
quaternary ammonium surfactants in a compatible diluent. A  
particularly useful application of the present invention is in  
15       hair care compositions, especially rinse-off hair conditioning  
and/or styling compositions.

**BACKGROUND OF THE INVENTION**

20       Typical hair conditioning products have a particular thick  
rheology that is desirable for such products. These products are  
based on the combination of a surfactant, which is generally a  
quaternary ammonium compound, and a fatty alcohol. This  
combination results in a gel-network structure which provides the  
composition with a thick rheology. However, while such  
compositions deliver conditioning benefits to the hair, such  
25       compositions also deposit on hair making hair look and feel dirty.

30       Alternative thickening systems have been used in hair care  
compositions, but none have been found to date which provide this  
same desirable rheology. Though hair care products thickened with  
polymer thickeners can be made to have a thick rheology, these  
products generally are characterized by an undesirable "slimy"  
feel and do not hold their poured shape.

35       Nonionic water-soluble cellulose ethers are employed in a  
variety of applications, including hair care compositions. Widely  
used, commercially-available nonionic cellulose ethers include  
methyl cellulose, hydroxy propyl methyl cellulose, hydroxyethyl

cellulose, hydroxypropyl cellulose and ethyl hydroxyethyl cellulose.

5 Better thickening efficiency is realized with higher molecular weight cellulose ethers. However, production of such materials is difficult and expensive. Though crosslinking of these polymers is an alternative means to achieve high viscosity solutions, good crosslinking techniques are not known. Of course, high concentrations of polymers will also provide high viscosity but such an approach is inefficient and impractical, particularly  
10 due to the high expense involved. Furthermore, use of highly crosslinked polymers or high levels of polymeric thickeners may result in a vehicle system that is too elastic for the present uses.

15 Alternative water-soluble polymeric thickeners sometimes used to thicken hair care compositions are natural polysaccharides such as guar gum, xanthan gum and locust bean gum.

A number of references teach the use of nonionic cellulose ethers and water-soluble gums for thickening hair care compositions. See for example, U.S. Patent 4,557,928, Glover, issued  
20 December 10, 1985, teaching a hair conditioner comprising a suspension system which consists of one of glucan gum, guar gum, and hydroxyethylcellulose; and U.S. Patent 4,581,230, Grollier et al., issued April 8, 1986, which teaches cosmetic compositions for treating hair which comprise as thickening agents hydroxyethyl-  
25 cellulose, or water-soluble vegetable thickening agents, such as guar gum. Japanese Patent Publication 61-053211, published March 7, 1986, discloses a hair colorant containing an aromatic alcohol, xanthan gum, and hydroxyethylcellulose.

Certain cellulose ethers have been disclosed in U.S. Patent  
30 4,228,277, Landoll, issued October 14, 1980, which are relatively low molecular weight but which are capable of producing highly viscous aqueous solutions in practical concentrations. These materials are nonionic cellulose ethers having a sufficient degree of nonionic substitution selected from the group consisting of  
35 methyl, hydroxyethyl, and hydroxypropyl to cause them to be

water-soluble and which are further substituted with a hydrocarbon radical having from about 10 to 24 carbon atoms in an amount between about 0.2 weight percent and the amount which renders said cellulose ether less than 1%, by weight, soluble in water. The  
5 cellulose ether to be modified is preferably one of low to medium molecular weight; i.e., less than about 800,000 and preferably between about 20,000 and 700,000 (about 75 to 2500 D.P.).

These modified cellulose ethers have been disclosed for use in a variety of composition types. Landoll ('277) teaches the use  
10 of these materials in shampoo formulations. Hercules trade literature teaches the use of these materials in shampoos, liquid soaps, and lotions. U.S. Patent 4,683,004, Goddard, issued July 28, 1987, discloses the use of these materials in mousse compositions for the hair. U.S. Patent 4,485,089, Leipold, issued  
15 November 27, 1984, teaches dentifrice compositions containing these materials.

These materials have now been found to provide a rheology very much like the desirable gel-network structure of typical hair conditioners (without the slimy feel associated with most poly-  
20 meric thickeners), when they are combined with surfactants at certain critical levels. Such compositions are disclosed in U.S. Serial Nos. 07/551,118, 07/551,119, and 07/551,120, all filed July 16, 1990, by Bolich, Norton, and Russell.

Still, it remains desirable to provide further improved  
25 vehicle systems for use for cosmetic compositions. In particular, it is desirable to improve perceived spreadability of the compositions upon application by the user to the hair or skin. It is also desirable to provide improved wet feel of the hair on skin treated with such cosmetic compositions.

Hence, it is an object of the present invention to provide a  
30 vehicle system for a hair care and other cosmetic composition which provides a gel-network-like structure to the composition not based on a typical quaternary ammonium compound/fatty alcohol gel-network thickening system, which provides improved perceived  
35

spreadability upon application to the skin or hair and which provides improved wet feel of the hair or skin to the touch.


It is also an object of the present invention to provide a vehicle system, as described above, for a hair care and other cosmetic compositions which allows for dispersion of a wide variety of active hair or skin care components therein while providing improved wet feel and perceived spreadability relative to such compositions with prior disclosed vehicle systems.

In a particular aspect of this patent, it is an object to provide hair styling/conditioning compositions having excellent wet hair feel. Such compositions contain hair setting agents which typically should be accompanied by a distributing aid to facilitate spreading of the hair setting agent upon application to hair. The use of distributing aids, such as xanthan gum, unfortunately can negatively impact wet hair feel. Thus it is another object of this invention to provide a hair styling and conditioning composition containing a distributing aid for the hair setting agent that has excellent wet hair feel characteristics.


These and other objects will become readily apparent from the detailed description which follows.

#### SUMMARY OF THE INVENTION

The present invention relates to vehicle systems for use in cosmetic compositions which are polymer-based but which provide a rheology to the cosmetic compositions which mimics gel-network systems. These vehicle systems comprise a two component thickening system in a compatible diluent, wherein the primary thickener component is hydrophobically modified, nonionic, long chain alkoxylated polymer that is soluble in the diluent and the second thickener component is selected from quaternary ammonium surfactants having the formula, in salt form:



wherein X is a salt-forming anion,  $z$  is the ionic charge of X, the quaternary ammonium radicals  $R_1$ ,  $R_2$ ,  $R_3$ , and  $R_4$  independently are  $C_1 - C_{22}$  alkyl,  $C_{14} - C_{22}$  alkyl amido  $C_2 - C_6$  alkylene, or benzyl, and from two to three of said quaternary ammonium radicals, preferably two, are  $C_{14} - C_{22}$  alkyl or  $C_{14} - C_{22}$  alkyl amido  $C_2 - C_6$  alkylene (preferably  $C_2 - C_3$  alkylene), preferably  $C_{16} - C_{22}$  alkyl, more preferably  $C_{18} - C_{22}$  alkyl, or mixtures thereof, no more than two of said radicals are either  $C_{14} - C_{22}$  alkyl amido  $C_2 - C_6$  alkylene or a combination of  $C_{14} - C_{22}$  alkyl and  $C_{14} - C_{22}$  alkyl amido  $C_2 - C_6$  alkylene, from one to two of said quaternary ammonium radicals, preferably two, are  $C_1 - C_6$  alkyl, preferably  $C_1 - C_3$  alkyl, more preferably methyl, and no more than one of said radicals is benzyl; or



wherein X and a are as defined above, the radicals R<sub>1</sub>, R<sub>2</sub>, and R<sub>3</sub> independently are C<sub>1</sub>-C<sub>22</sub> alkyl or benzyl, preferably C<sub>1</sub>-C<sub>22</sub> alkyl, and two or three of said radicals are C<sub>14</sub>-C<sub>22</sub> alkyls, preferably C<sub>16</sub>-C<sub>22</sub> alkyl, or C<sub>14</sub>-C<sub>22</sub> alkyl amido C<sub>2</sub>-C<sub>6</sub> alkylene (preferably C<sub>2</sub>-C<sub>3</sub> alkylene), or a mixture thereof, zero or one of said radicals are C<sub>1</sub>-C<sub>6</sub> alkyl, preferably C<sub>1</sub>-C<sub>3</sub> alkyl, more preferably methyl, zero or one of said radicals is benzyl; or a mixture of Formula I and II surfactants; wherein the quaternary ammonium surfactant component of the above description has a sufficient level unsaturation in the C<sub>14</sub>-C<sub>22</sub> alkyl or C<sub>14</sub>-C<sub>22</sub> alkyl amido C<sub>2</sub>-C<sub>6</sub> alkylene radicals, or mixtures thereof, such that average iodine value of said component is at least about 15.

More specific embodiments of the cosmetic compositions of the present invention comprise:

(a) from about 80% to about 100%, preferably from about 80% to about 99.9%, of a vehicle system which comprises:

- 6 -

- 5 (A) from about 0.1% to about 10% by weight of the cosmetic composition of a hydrophobically modified nonionic water-soluble polymer which comprises a water-soluble polymer backbone and hydrophobic groups selected from the group consisting of C<sub>8</sub>-C<sub>22</sub> alkyl, aryl alkyl, alkyl aryl groups and mixtures thereof; wherein the ratio of hydrophilic portion to hydrophobic portion of the polymer is from about 10:1 to about 1000:1; preferably the hydrophobically modified nonionic water-soluble polymer comprises a nonionic cellulose ether having a sufficient degree of nonionic substitution selected from the group consisting of methyl, hydroxyethyl, and hydroxypropyl to cause it to be water-soluble and being further substituted with a long chain alkyl radical having 10 to 24 carbon atoms in an amount between about 0.2 weight percent and the amount which renders said cellulose ether less than 0.2, preferably less than 1%, by weight soluble in water;
- 10
- 15
- 20
- (B) from about 0.02% to about 5.0% by weight of the cosmetic composition of unsaturated quaternary ammonium surfactant as described above; and
- 25 (C) from about 65% to about 99% by weight of the cosmetic composition of a compatible diluent, said nonionic water-soluble polymer being soluble in said diluent; and
- (b) from 0 to about 20%, preferably from about 0.1% to about 20%, of an additional active cosmetic component;
- 30 wherein compositions comprising said vehicle system comprise no more than about 1.0%, preferably no more than about 0.5%, of water-soluble surfactant materials (at 25°C).

The unsaturated cationic quaternary ammonium surfactant as set forth above, can provide improved perceived spreading and improved wet feel of the hair or skin upon application by the

35




- 7 -

user. These vehicle systems are particularly useful in hair care compositions especially rinse-off hair conditioners and styling/conditioners.


5 In another aspect of this invention, hair styling and conditioning compositions suitable for rinse-off application are provided with yet further improved wet hair feel. These compositions contain a two component thickening system in a compatible solvent as described above and a hair setting agent dispersed in the composition, a distributing aid for the hair setting agent, 10 and additionally comprise as an essential ingredient a mono-long chain, tri-short chain cationic ammonium quaternary surfactant wherein the long chain is selected from C<sub>14</sub>-C<sub>22</sub> alkyl or C<sub>14</sub>-C<sub>22</sub> alkyl amido C<sub>2</sub>-C<sub>6</sub> alkylene and the short chains independently are selected from the group consisting of C<sub>1</sub>-C<sub>6</sub> alkyl and benzyl, with 15 the number of benzyl radicals per molecule being zero or 1.

More specific embodiments of these hair styling and conditioning compositions comprise:

- (a) from about 80% to about 99.5% of a vehicle system comprising:
- 20 (A) from about 0.1% to about 10.0% by weight of the cosmetic composition of a hydrophobically modified nonionic water-soluble polymer which comprises a water-soluble polymer backbone and hydrophobic groups selected from the group consisting of C<sub>8</sub>-C<sub>22</sub> 25 alkyl, aryl alkyl, alkyl aryl groups and mixtures thereof; wherein the ratio of the hydrophilic portion to the hydrophobic portion of the polymer is from about 10:1 to about 1000:1; and
- (B) from about 0.02% to about 10.0% by weight of the 30 cosmetic composition of unsaturated quaternary ammonium surfactant component of the formula:



wherein X is a salt-forming anion, a is the ionic charge of X, the quaternary ammonium radicals R<sub>1</sub>, R<sub>2</sub>, R<sub>3</sub>, and R<sub>4</sub> independently are C<sub>1</sub> - C<sub>22</sub> alkyl, C<sub>14</sub> - C<sub>22</sub> alkyl amido C<sub>2</sub> - C<sub>6</sub> alkylene, or benzyl, and from two to three of said quaternary ammonium radicals, are C<sub>14</sub>-C<sub>22</sub> alkyl or C<sub>14</sub>-C<sub>22</sub> alkyl amido C<sub>2</sub>-C<sub>6</sub> alkylene or mixtures thereof, no more than two of said radicals being C<sub>14</sub>-C<sub>22</sub> alkyl amido C<sub>2</sub>-C<sub>6</sub> alkylene or a combination of C<sub>14</sub>-C<sub>22</sub> alkyl and C<sub>14</sub>-C<sub>22</sub> alkyl amido C<sub>2</sub>-C<sub>6</sub> alkylene, from one to two of said quaternary ammonium radicals are C<sub>1</sub>-C<sub>6</sub> alkyls, and no more than one of said radicals is benzyl; or




wherein X is a salt-forming anion, a is the ionic charge of X, radicals R<sub>1</sub>, R<sub>2</sub>, and R<sub>3</sub> independently are C<sub>1</sub>-C<sub>22</sub> alkyl or benzyl, and two or three of said radicals are C<sub>14</sub>-C<sub>22</sub> alkyl, or C<sub>14</sub>-C<sub>22</sub> alkyl amido C<sub>2</sub> C<sub>6</sub> alkylene or a mixture thereof, zero or one of said radicals are C<sub>1</sub>-C<sub>6</sub> alkyl, zero or one of said radicals is benzyl, or a mixture of Formula I and II surfactants; wherein said the quaternary ammonium surfactant component has a sufficient level of unsaturation in the C<sub>14</sub>-C<sub>22</sub> alkyl or C<sub>14</sub>-C<sub>22</sub> alkyl amido C<sub>2</sub>-C<sub>6</sub> alkylene radicals, or mixture thereof, such that average iodine value of said component is at least 15; and

- (C) from about 65% to about 99% by weight of the cosmetic composition of a compatible diluent; and
- (b) from 0.05% to about 10%, by weight of the composition, of a hair setting agent;

- 9 -

- (c) from about 0.01% to about 5% of a distributing aid; and  
 (d) from about 0.05% to about 1.0%, by weight of the composition, of a mono-long chain, tri-short chain quaternary ammonium surfactant of the formula:



wherein X is a salt forming anion, a is the ionic charge of X, the quaternary ammonium radical  $R_1$  is  $C_{14}-C_{22}$  alkyl or  $C_{14}-C_{22}$  alkyl amido  $C_2-C_6$  alkylene, and quaternary ammonium radicals  $R_2$ ,  $R_3$ , and  $R_4$  independently are  $C_1-C_6$  alkyl or benzyl, wherein zero or one of said  $R_2$ ,  $R_3$ , and  $R_4$  radicals is benzyl;

wherein said composition comprises no more than about 1.0% of water-soluble surfactants.

The compositions hereof comprise or, alternately, can consist essentially of or consist of the essential ingredients, as well as the optional ingredients, described herein.

#### DETAILED DESCRIPTION OF THE INVENTION

The essential as well as various optional components of the present compositions are described below. All solubilities are determined at 25°C, unless otherwise indicated. All percentages and ratios are by weight unless otherwise indicated. All percentages are by weight of the total composition, unless otherwise indicated.

#### Hydrophobically Modified Water Soluble Polymer

The vehicle systems of the present invention contain, as an essential thickener component, a water soluble polymer. This thickening material is a hydrophobically modified nonionic water-soluble polymer. By "hydrophobically modified nonionic water-soluble polymer" is meant a nonionic water-soluble polymer which

- 10 -

has been modified by the substitution with a sufficient amount of hydrophobic groups to make the polymer less soluble in water. Hence, the polymer backbone can be essentially any water-soluble polymer. For the compositions hereof, the unmodified polymer backbone should be sufficiently soluble such that forms a substantially clear solution when dissolved in water at a level of 1%, by weight of the solution, at 25°C. The hydrophobic groups can be C<sub>8</sub> to C<sub>22</sub> alkyl, aryl alkyl, alkyl aryl groups and mixtures thereof. The degree of hydrophobic substitution on the polymer backbone should be from about 0.10% to about 1.0%, by total weight of the polymer, preferably from about .4% to about .7%. More generally, the ratio of hydrophilic portion to hydrophobic portion of the polymer is from about 10:1 to about 1000:1.

A number of existing patents disclose nonionic polymer materials which meet the above requirements and which are useful in the present invention. U.S. Patent 4,496,708, Dehm et al., issued January 29, 1985, teaches water-soluble polyurethanes having hydrophilic polyether backbones and pendant monovalent hydrophobic groups to result in a hydrophilic/lipophilic balance of between about 14 and about 19.5. U.S. Patent 4,426,485, Hoy et al., issued January 17, 1984, discloses a water-soluble thermoplastic organic polymer having segments of bunched monovalent hydrophobic groups. U.S. Patent 4,415,701, Bauer, issued November 15, 1983, discloses copolymers containing a monoepoxide and a dioxolane.

The most preferred hydrophobically modified water soluble polymeric thickener materials for use in the present invention are disclosed in U.S. Patent 4,228,277, Landoll, issued October 14, 1980, which is incorporated herein by reference. The materials disclosed therein are thickeners comprising a nonionic long chain alkylated cellulose ether.

The cellulose ethers have a sufficient degree of nonionic substitution selected from the group consisting of methyl, hydroxyethyl and hydroxypropyl to cause them to be water-soluble. The cellulose ethers are further substituted with a hydrocarbon

- 11 -

radical having about 10 to 24 carbon atoms in an amount between about 0.2 weight percent and the amount which renders said cellulose ether less than 0.2%, preferably less than 1%, by weight, soluble in water. The cellulose ether to be modified is  
5 preferably one of low to medium molecular weight, i.e., less than about 800,000 and preferably between about 20,000 and 700,000 (about 75 to 2500 D.P.).

The Landoll patent teaches that any nonionic water-soluble cellulose ether can be employed as the cellulose ether substrate.  
10 Thus, e.g., hydroxyethyl cellulose, hydroxypropyl cellulose, methyl cellulose, hydroxypropyl methyl cellulose, ethyl hydroxyethyl cellulose, and methyl hydroxyethyl cellulose can all be modified. The amount of nonionic substituent such as methyl, hydroxyethyl or hydroxypropyl is taught not to be critical so long  
15 as there is an amount sufficient to assure that the ether is water-soluble.

The preferred cellulose ether substrate is hydroxyethyl cellulose (HEC) of about 50,000 to 700,000 molecular weight. Hydroxyethyl cellulose of this molecular weight level is the most  
20 hydrophilic of the materials contemplated. It can thus be modified to a greater extent than can other water-soluble cellulose ether substrates before insolubility is achieved. Accordingly, control of the modification process and control of the properties of the modified product can be more precise with this substrate.  
25 Hydrophilicity of the most commonly used nonionic cellulose ethers varies in the general direction: hydroxyethyl → hydroxypropyl → hydroxypropyl methyl → methyl.

The long chain alkyl modifier can be attached to the cellulose ether substrate via an ether, ester or urethane linkage. The  
30 ether linkage is preferred.

Although the materials taught in Landoll are referred to as being "long chain alkyl group modified", it will be recognized that except in the case where modification is effected with an alkyl halide, the modifier is not a simple long chain alkyl group.  
35 The group is actually an alphahydroxyalkyl radical in the case of

- 12 -

an epoxide, a urethane radical in the case of an isocyanate, or an acyl radical in the case of an acid or acyl chloride. Nonetheless, the terminology "long chain alkyl group" is used since the size and effect of the hydrocarbon portion of the modifying molecule completely obscure any noticeable effect from the connecting group. Properties are not significantly different from those of the product modified with the simple long chain alkyl group.

Methods for making these modified cellulose ethers are taught in Landoll ('277) at column 2, lines 36-65.

These materials have been found to be particularly desirable for use in the vehicle systems of the cosmetic compositions of the present invention. The materials are able to stabilize suspensions of dispersed phases, and when used with the additional components in the vehicle systems of the present invention, they produce rheologically thick products which lack the slimy feel characteristic of most polymeric thickeners.

One commercially available material which meets these requirements is NATROSOL PLUS Grade 330, a hydrophobically modified hydroxyethylcellulose available from Aqualon Company, Wilmington, Delaware. This material has a  $C_{16}$  alkyl substitution of from about 0.4% to about 0.8% by weight. The hydroxyethyl molar substitution for this material is from about 3.0 to about 3.7. The average molecular weight for the water-soluble cellulose prior to modification is approximately 300,000. Another material of this type has a  $C_{16}$  alkyl substitution of from about 0.40% to about 0.95%, by weight. The hydroxyethyl molar substitution for this material is from about 2.3 to about 3.3, and may be as high as about 3.7. The average molecular weight for the water soluble cellulose prior to modification is approximately 700,000.


The hydrophobically modified water soluble polymer thickener component is present in the cosmetic compositions of the present invention at from about 0.1% to about 10.0%, preferably from about 0.2% to about 5.0%.

- 13 -

Unsaturated Quaternary Ammonium Surfactant

The present vehicle systems further comprise, as a second essential component, a second thickener which is an unsaturated water-insoluble, C<sub>14</sub>-C<sub>22</sub> alkyl-substituted quaternary ammonium surfactant. By "water-insoluble surfactant" is meant surfactant materials which do not form clear isotropic solutions when dissolved in water at greater than 0.2 weight percent at 25°C. By "unsaturated" as applied to the C<sub>14</sub>-C<sub>22</sub> alkyl substituted quaternary ammonium surfactant is meant quaternary ammonium surfactants having a sufficient amount of unsaturation such that it has an iodine value of at least about 15. Generally, the iodine value will be from about 20 to about 200. It should be understood that the iodine value is meant to describe the average level of unsaturation of the essential C<sub>14</sub>-C<sub>22</sub> alkyl substituted quaternary ammonium surfactant. "Alkyl" as used herein, includes unsaturated radicals as well as saturated.


The essential C<sub>14</sub>-C<sub>22</sub> alkyl-substituted quaternary ammonium surfactant component hereof constitutes materials of the formula, in salt form:



wherein X is a salt-forming anion, a is the ionic charge of X, the quaternary ammonium radicals R<sub>1</sub>, R<sub>2</sub>, R<sub>3</sub>, and R<sub>4</sub> independently are C<sub>1</sub> - C<sub>22</sub> alkyl, C<sub>14</sub> - C<sub>22</sub> alkyl amido C<sub>2</sub> - C<sub>6</sub> alkylene, or benzyl, and from two to three of said quaternary ammonium radicals, preferably two, are C<sub>14</sub>-C<sub>22</sub> alkyl or C<sub>14</sub>-C<sub>22</sub> alkyl amido C<sub>2</sub>-C<sub>6</sub> alkylene (preferably C<sub>2</sub>-C<sub>3</sub> alkylene), preferably C<sub>14</sub>-C<sub>22</sub> alkyl, more preferably C<sub>18</sub>-C<sub>18</sub> alkyl, or mixtures thereof, no more than two of said radicals are either C<sub>14</sub>-C<sub>22</sub> alkyl amido C<sub>2</sub>-C<sub>6</sub> alkylene or a combination of C<sub>14</sub>-C<sub>22</sub> alkyl and C<sub>14</sub>-C<sub>22</sub> alkyl amido C<sub>2</sub>-C<sub>6</sub> alkylene, from one to two of said quaternary ammonium radicals, preferably two, are C<sub>1</sub>-C<sub>6</sub> alkyls, preferably C<sub>1</sub>-C<sub>3</sub> alkyl, more

- 14 -

preferably methyl, and no more than one of said radicals is benzyl; or



10 wherein X and a are as defined above, the radicals R<sub>1</sub>, R<sub>2</sub>, and R<sub>3</sub> independently are C<sub>1</sub>-C<sub>22</sub> alkyl or benzyl, preferably C<sub>1</sub>-C<sub>22</sub> alkyl, and two or three of said radicals, preferably two, are C<sub>14</sub>-C<sub>22</sub> alkyl, preferably C<sub>16</sub>-C<sub>22</sub> alkyl, or C<sub>14</sub>-C<sub>22</sub> alkyl amido C<sub>2</sub>-C<sub>6</sub> alkylene (preferably C<sub>2</sub>-C<sub>3</sub> alkylene), or a mixture thereof, zero or one of said radicals are C<sub>1</sub>-C<sub>6</sub> alkyl, preferably C<sub>1</sub>-C<sub>3</sub> alkyl, more preferably methyl, zero or one of said radicals is benzyl, or  
15 a mixture of Formula I and II surfactants; wherein the quaternary ammonium surfactant component of the above description has a sufficient level unsaturation in the C<sub>14</sub>-C<sub>22</sub> alkyl or C<sub>14</sub>-C<sub>22</sub> alkyl amido C<sub>2</sub>-C<sub>6</sub> alkylene radicals, or mixtures thereof, such that average iodine value of said component is at least about 15.

20 The anion X can be any salt-forming anion suitable for use in cosmetic compositions. Suitable anions include halogens (especially chloride and bromide), acetate, phosphate, nitrate, sulfate, and alkyl sulfate. Preferred anions generally are chloride, acetate, sulfate, and methyl sulfate.

25 Examples of unsaturated quaternary ammonium surfactants hereof include the salts of dimethyl di(unsaturated) tallow ammonium, dimethyl distearyl ammonium, dimethyl di(unsaturated)-arachidyl ammonium, dioleyl dimethylammonium, di-rapeseed alkyl dimethyl ammonium, diricinoleyl dimethyl ammonium, and disoyadi-  
30 monium, olealkonium.

Other examples include the salts of methyl-1-oleyl amido ethyl-2-oleyl imidazolinium, dierucyl dimethyl ammonium, and methyl-1-soya amido ethyl-2-soya imidazolinium.

35 It will be recognized by those skilled in the art that unsaturated quaternary ammonium surfactants, when purchased



- 15 -

commercially, will normally also contain saturated quaternary ammonium surfactants of otherwise similar structure. An example of this is ADOGEN 470, commercially available from Sherex Chemical Company (Dublin, Ohio, USA), which contains a mixture of saturated and unsaturated ditallow dimethyl ammonium chloride. Compositions containing such materials are included within the scope of this invention as long as they contain the minimum level of surfactant defined herein having a level of unsaturation of surfactant falling within Formula (I) and (II) is sufficient such that the average iodine value is at least about 15.

This quaternary ammonium surfactant hereof is used at a level of from about 0.02% to about 10.0%, preferably from about 0.05% to about 3.0%, more preferably from about 0.05% to about 2.0%, by weight, of the composition.

Whereas the water insoluble unsaturated quaternary ammonium surfactant component hereof is referred to as a thickener material, it should also be recognized that it can also act as a conditioner for the hair and/or skin.

#### Diluent

A third essential component in the vehicle systems of the present invention is a diluent which is a solvent for the hydrophobically modified water-soluble polymer and is compatible with the other components in the present compositions. Generally the diluent will comprise water or a water-lower alkanol (e.g., C<sub>2</sub>-C<sub>4</sub> alcohols) mixture; preferably it will include at least about 25%, more preferably at least about 50%, even more preferably at least about 75%, by total weight of the diluent, of water. Rinse-off compositions, such as hair rinses, preferably utilize water as the diluent. The diluent is present in the compositions of the present invention at a level of from about 65% to about 99% by weight of the cosmetic composition.

The other vehicle components are dispersed or mixed in the diluent to provide an optimum thick rheology to cosmetic compositions formulated therewith which mimics the gel-network rheology of typical hair conditioning compositions. This rheology is

- 16 -

characterized by a shear stress of from 0 to about 50 pascal, over a shear rate range of  $0.04 \text{ sec}^{-1}$  to  $25 \text{ sec}^{-1}$ . The rheology is measured using a Bohlin Rheometer VOR with the following cone and plate set-up: cone has a 2.5 degree angle, plate is 30mm in diameter, the gap between the truncated cone and plate is set at  $70 \mu\text{m}$ , and the torque bar used is 20.148 g-cm. The sample amount is 0.35ml and the sample is syringed onto the center of the plate. The system used is as follows: there is no initial delay time, the strain delay time is 25 sec, the integration time is 5 sec, the sensitivity is set at 1X, the shear sweep is up, the shear range is from about  $0.0405 \text{ sec}^{-1}$  to  $25.53 \text{ sec}^{-1}$  (shear No. = 11 to 39), and the temperature is maintained constant between series at ambient temperature ( $20^\circ\text{C}$  to  $25^\circ\text{C}$ ).

#### Additional Thickener

The present vehicle systems can also comprise an additional thickening component, such as water-soluble polymeric materials other than the hydrophobically modified water soluble polymers described above. Examples of water-soluble polymers which may desirably be used as an additional thickening component in the present vehicle systems, are hydroxyethylcellulose, hydroxypropyl cellulose, hydroxypropyl methylcellulose, polyethylene glycol, polyacrylamide, polyacrylic acid, polyvinyl alcohol, polyvinyl pyrrolidone K-120, dextrans, for example Dextran purified crude Grade 2P, available from D&O Chemicals, carboxymethyl cellulose, plant exudates such as acacia, ghatti, and tragacanth, seaweed extracts such as sodium alginate, propylene glycol alginate and sodium carrageenan, and UCARE JR-polymer (a cationic modified hydroxyethyl cellulose available from Union Carbide). Preferred as the optional additional thickener for the present vehicle systems are natural polysaccharide materials. Examples of such materials are guar gum, locust bean gum, and xanthan gum. Also preferred as the additional thickener in the present compositions is hydroxyethyl cellulose having a molecular weight of about 700,000. It is preferred that these polymer materials not contain

35

- 17 -

cellulose as this may interfere with obtaining optimum viscosities.

5 The additional thickening component, if present in the cosmetic compositions of the present invention, is preferably used at a level of from about 0.3% to about 5.0%, preferably from about 0.4% to about 3.0%.

#### Distributing Aid

10 An additional component in the vehicle systems of the present invention is a material which acts as a distributing aid for the composition. Such a material helps to distribute the cosmetic composition onto the hair or skin avoiding localized deposition of the active component onto the hair or skin. Without such a component in a composition, some active components in the composition would not be deposited and spread out as evenly, and hence, 15 would not be quite as effective. In particular, a distributing aid is especially useful if ingredients that are tacky are included, such as hair setting polymers.

Distributing aid materials useful in the present invention are actually a subclass of the class of materials that can be used 20 as the optional water-soluble polymer additional thickener in the present invention. This subclass is defined as follows: water-soluble polymer materials having high molecular weight, i.e., greater than 1,000,000; and/or strong ionic character. By strong ionic character is meant that the material conducts electricity at 25 greater than 30 millivolts. This can be measured by evaluating conductance of a 1% solution of polymer in DRO (double reverse osmosis) water preserved with 0.03% Kathon CG (methylchloroisothiazolinone and methylisothiazolinone, a preservative available from Rohm & Haas) using a calibrated Corning 130 pH meter. The probes used were as follows: the reference electrode is an Orion 30 Model 9001 single junction. The pH electrode is an Orion Model 9161, silver-silver chloride. The probes are set 3/8 of an inch apart. The pH meter is set to millivolt readings. The absolute measurement is recorded after 4 minutes immersion.

35

Examples of water soluble polymer materials which meet these requirements and hence, can act as distributing aids in the present compositions include xanthan gum; Dextran purified crude Grade 2P available from D&O chemicals; carboxymethyl celluloses; for example, CMC's 4H1F, 4M6F, 7HF, 7M8SF, 7LF, 9H4F, 9M8, 12M8P, 16M31, (all available from Aqualon); plant exudates such as acacia, ghatti and tragacanth; seaweed extracts such as sodium alginate, propylene glycol alginate, and sodium carrageenan; high molecular weight hydroxyethyl celluloses such as Natrosol 250H and Natrosol 250HHR (available from Aqualon); and pectin.

Because the class of materials which may act as distributing aids in the present invention is a subset of the optional water-soluble additional thickener, the materials in this subclass may be used to provide both benefits to the composition. For example, xanthan gum is a water-soluble natural polysaccharide material which additionally has a high molecular weight. Hence, this material could be used by itself to provide both additional thickening benefits and distributing benefits. However, it may be necessary to use such materials at slightly higher levels to provide both benefits.

It is also possible to use two separate materials as the optional water-soluble polymer additional thickener and the distributing aid of the present invention. This would be done when the water-soluble polymer additional thickener was not a high molecular weight material or of strong ionic character. Locust bean gum is such a material. A distributing aid such as xanthan gum could be used with locust bean gum to provide the additional distributing benefits.

If a distributing aid is present in the cosmetic compositions of the present invention, it should be present at a level of from about 0.02% to about 2.5%, preferably from about 0.05% to about 1.0%, of the cosmetic composition. If the distributing aid is bifunctional, i.e., acting as both the optional additional thickener and the distributing aid it should be present at a level of from about 0.2% to about 5% of the composition. Thus, in general,

the distributing aid will be used at a level of about 0.02% to about 5%.

5 A distributing aid is particularly useful in hair care compositions of the present invention especially rinse-off hair conditioners. The distributing aid helps to spread some hair conditioning components, especially hair setting agents, evenly over the hair.

10 The present vehicle systems and cosmetic compositions formulated therewith should be substantially free of water-soluble surfactants. These materials are not compatible with the vehicle systems of the present composition. By "substantially free of water-soluble surfactants" is meant that the compositions comprise less than an amount of such surfactants that will destroy the present unique desirable rheology that is the object of the  
15 prevent invention. Generally, this will mean that the present compositions comprise no more than about 1%, preferably no more than about 0.5%, of such materials. Examples of specific water-soluble surfactant materials that can be particularly harmful to the present vehicle systems are alkyl sulfates and ethoxylated  
20 alkyl sulfates, such as ammonium lauryl sulfate; amphoteric surfactants which are derivatives of aliphatic secondary and tertiary amines; nonionic surfactants produced by the condensation of alkylene oxide groups with an organic hydrophilic compound, such as laureth-23 (sold under the trademark Brij 35 by ICI  
25 Americas); and high alkyl betaines, sulfo betaines, amido betaines and amido sulfobetaines, such as cetyl betaine.

The present vehicle systems and cosmetic compositions formulated therewith are also preferably substantially free of fatty alcohol materials, such as stearyl-, cetyl-, myristyl-, behenyl-,  
30 lauryl-, and oleyl alcohol. By "substantially free of fatty alcohol materials" is meant that the compositions of the present invention comprise no more than about 1% of these materials. These materials are commonly used in vehicle systems for hair conditioner products. However, these materials tend to deposit on  
35 the hair and leave the hair feeling dirty after use. These

materials are not required in the present vehicle systems, as they are thickened with alternative materials which do not deposit on hair.

5 The present vehicle systems can be used in essentially any cosmetic products having a thick gel-network type rheology and which are used to deliver some active component onto the hair or skin. Such compositions would include skin moisturizing lotions, sunscreen compositions, and skin cleansing compositions. However, cosmetic compositions most desirably used with the present vehicle  
10 systems are hair care products, especially rinse-off hair care products where some active hair care component is to be deposited onto the hair but the vehicle carrying that component is desirably rinsed off of the hair with little or no deposition of the vehicle material onto the hair.

15 Generally, the present vehicle systems will not be useful in typical shampoo compositions since these compositions contain high levels of water-soluble surfactants, which as discussed *supra*, are incompatible with the present vehicle systems. However, the present vehicle systems are useful in typical hair coloring  
20 compositions, hair tonic or gel compositions, hair mousse compositions, and especially hair conditioning compositions.

#### Active Cosmetic Component

The cosmetic compositions of the present invention generally will comprise an additional active cosmetic component which  
25 provides some benefit to the hair or skin. The term "additional active component" is used since the unsaturated quaternary ammonium surfactant component hereof generally operates as a conditioner to hair or skin. Such materials may include moisturizing agents, sunscreen agents, cleaning agents (that are compatible with the  
30 present vehicle systems), and especially hair conditioning agents, hair styling agents, antidandruff agents, hair growth promoters, hair dyes and pigments, or perfumes.

A wide variety of conventional suncreening agents are suitable for use in the cosmetic compositions of the present  
35 invention. Segarin, et al., at Chapter VIII, pages 189 et seq.,

of Cosmetics Science and Technology, disclose numerous suitable agents. Specific suitable sunscreens agents include, for example: p-aminobenzoic acid, its salts and its derivatives; anthranilates; salicylates; cinnamic acid derivatives; dihydroxy-  
5 cinnamic acid derivatives; trihydroxycinnamic acid derivatives; hydrocarbons; dibenzalacetone and benzalacetophenone; naphthol-sulfonates; dihydroxy-naphtholic acid and its salts; coumarin derivatives; diazoles; quinine salts; quinoline derivatives; hydroxy- or methoxy-substituted benzophenones; uric and vilouric  
10 acids; tannic acid and its derivatives; hydroquinone; and benzo-phenones.

Of these, 2-ethylhexyl p-methoxycinnamate, 4,4'-t-butyl methoxydibenzoylmethane, 2-hydroxy-4-methoxybenzophenone, octyl-dimethyl p-aminobenzoic acid, digalloyltriolate, 2,2-dihydroxy-  
15 4-methoxybenzophenone, ethyl-4-[bis(hydroxypropyl)]-aminobenzoate, 2-ethylhexyl-2-cyano-3,3-diphenylacrylate, 2-ethylhexylsalicylate, glyceryl p-aminobenzoate, 3,3,5-trimethylcyclohexylsalicylate, methylanthranilate, p-dimethyl-aminobenzoic acid or aminobenzoate, 2-ethylhexyl p-dimethylaminobenzoate, 2-phenylbenzimidazole-5-  
20 sulfonic acid 2-(p-dimethyl-aminophenyl)-5-sulfonicbenzoxazoic acid, and mixtures of these compounds are particularly useful.

Examples of antidandruff aids suitable for use with the vehicle systems of the present invention include zinc pyrithione, sulphur, and selenium sulfide. One example of a hair growth  
25 promoter suitable for use with the vehicle systems of the present invention is Minoxidil, (6-amino-1, 2-dihydro -1-hydroxy-2-imino-4-piperidino pyrimide) available from Upjohn. Hair oxidizing (bleaching) agents, such as hydrogen peroxide, perborate and persulfate salts, and hair reducing agents such as  
30 thioglycolates may also be used.

#### Additional Conditioners

Examples of conditioning materials suitable for use in the vehicle systems of the present invention are volatile liquid hydrocarbons. These are particularly useful for use in hair  
35 treatments.


These materials preferably have a boiling point in the range of about 99°C to about 260°C and have a solubility in water of less than about 0.1%. The hydrocarbons may be either straight or branched chain and may contain from about 10 to about 16, preferably from about 12 to about 16 carbon atoms. Examples of suitable hydrocarbons are decane, dodecane, tetradecane, tridecane and mixtures thereof.

Volatile silicones useful as an active conditioning component in the compositions of the present invention include silicone fluids such as cyclic and linear polydimethylsiloxanes. The number of silicon atoms in the cyclic silicones is preferably from about 3 to about 7, more preferably 4 or 5.

The general formula for the cyclic silicones is



wherein  $n = 3-7$ . The linear polydimethylsiloxanes have from about 3 to 9 silicon atoms and have the general formula:



20 Silicones of the above type, both cyclic and linear, are available from Dow Corning Corporation, Dow Corning 344, 345 and 200 fluids; Union Carbide, Silicone 7202 and Silicone 7158; and Stauffer Chemical, SWS-03314.


25 The linear volatile silicones generally have viscosities of less than about 5 centipoise at 25°C while the cyclic materials have viscosities less than about 10 centipoise at 25°C. A description of volatile silicones is found in Todd and Byers, "Volatile Silicone Fluids for Cosmetics", *Cosmetics and Toiletries*, Vol. 91, January 1976, pp. 27-32, incorporated herein  
30 by reference.

The volatile agent may be present in the compositions of this invention at a level of from about 1% to about 20%, preferably from about 2% to about 15%. The volatile silicones are the preferred volatile agents.

35



Nonvolatile silicone fluids are useful as the active hair conditioning component in the compositions of the present invention. They will generally have a viscosity in excess of 10 centipoise at 25°C. Examples of such materials include polydimethylsiloxanes (fluids and gums) aminosilicones and phenylsilicones. These include polyalkyl or polyaryl siloxanes with the following structure:



wherein R is alkyl or aryl, and x is an integer from about 7 to about 8,000 may be used. A represents groups which block the ends of the silicone chains.


The alkyl or aryl groups substituted on the siloxane chain (R) or at the ends of the siloxane chains (A) may have any structure as long as the resulting silicones remain fluid at room temperature, are hydrophobic, are neither irritating, toxic nor otherwise harmful when applied to the hair, are compatible with the other components of the composition, are chemically stable under normal use and storage conditions, and are capable of being deposited on and of conditioning hair.

Suitable A groups include methyl, methoxy, ethoxy, propoxy, and aryloxy. The two R groups on the silicone atom may represent the same group or different groups. Preferably, the two R groups represent the same group. Suitable R groups include methyl, ethyl, propyl, phenyl, methylphenyl and phenylmethyl. The preferred silicones are polydimethyl siloxane, polydiethylsiloxane, and polymethylphenylsiloxane. Polydimethylsiloxane is especially preferred.

Suitable methods for preparing these silicone materials are disclosed in U.S. Patents 2,826,551 and 3,964,500 and references cited therein. Silicones useful in the present invention are also commercially available. Suitable examples include Viscasil, a trademark of the General Electric Company and silicones offered by


Dow Corning Corporation and by SWS Silicones, a division of Stauffer Chemical Company.

Other useful silicone materials include materials of the formula:



in which x and y are integers which depend on the molecular weight, the average molecular weight being approximately between 5,000 and 10,000. This polymer is also known as "amodimethicone".


Other silicone cationic polymers which can be used in the present composition correspond to the formula:



in which G is chosen from the group consisting of hydrogen, phenyl, OH, C<sub>1</sub>-C<sub>8</sub> alkyl and preferably methyl; a denotes 0 or an integer from 1 to 3, and preferably equals 0;

b denotes 0 or 1 and preferably equals 1; the sum n+m is a number from 1 to 2,000 and preferably from 50 to 150, n being able to denote a number from 0 to 1,999 and preferably from 49 to 149 and m being able to denote an integer from 1 to 2,000 and preferably from 1 to 10;


R<sub>1</sub> is a monovalent radical of formula C<sub>q</sub>H<sub>2q</sub>L in which q is an integer from 2 to 8 and L is chosen from the groups



in which R<sub>2</sub> is chosen from the group consisting of hydrogen, phenyl, benzyl, a saturated hydrocarbon radical, preferably an alkyl radical containing from 1 to 20 carbon atoms, and A<sup>-</sup> denotes a halide ion.


These compounds are described in greater detail in European Patent Application EP 95,238. An especially preferred polymer corresponding to this formula is the polymer known as "trimethylsilylamodimethicone" of formula:

5



15 Compositions of the present invention including this material typically will comprise up to about 1.0% of the trimethylsilylamodimethicone silicone conditioning material.

Other silicone cationic polymers may also be used in the present compositions, such as those of the formula:



25 in which R<sub>3</sub> denotes a monovalent hydrocarbon radical having from 1 to 18 carbon atoms, and more especially an alkyl or alkenyl radical such as methyl;

R<sub>4</sub> denotes a hydrocarbon radical such as, preferably a C<sub>1</sub>-C<sub>18</sub> alkylene radical or a C<sub>1</sub>-C<sub>18</sub>, and preferably C<sub>1</sub>-C<sub>8</sub>, alkyleneoxy radical;

30

Q<sup>-</sup> is a halide ion, preferably chloride;

r denotes an average statistical value from 2 to 20, preferably from 2 to 8;

s denotes an average statistical value from 20 to 200, and preferably from 20 to 50.

35

These compounds are described in greater detail in U.S. Patent 4,185,017.

A polymer of this class which is especially preferred is that sold by UNION CARBIDE under the name "UCAR SILICONE ALE 56".

5       Silicone conditioning agents are used in the present compositions at levels of from about 0.1% to about 18%, preferably from about 0.5% to about 15%.

10       Preferred silicone conditioning agents for use in the present compositions comprise combinations of volatile silicone fluids having viscosities of less than about 10 centipoise, and from about 0.015% to about 9.0%, preferably from about 0.5% to about 2.0%, of silicone gums having viscosities of greater than about 1,000,000 centipoise, at ratios of volatile fluid to gum of from about 90:10 to about 10:90, preferably from about 85:15 to about 15       50:50.

15       Alternative preferable nonvolatile silicone materials for use in the present invention comprise non-volatile silicone fluids having viscosities of less than about 100,000 cP (centipoise) at 25°C, and from about 0.015% to about 9.0%, preferably from about 20       0.5% to about 2.0%, of silicone gums having viscosities greater than about 1,000,000 cP at 25°C, especially polydimethylsiloxane gums and polyphenylmethylsiloxane gums, at ratios of non-volatile fluid to gum of from about 70:30 to about 30:70, preferably from about 60:40 to about 40:60.

25       The efficacy of nonvolatile silicone hair conditioning agents can be enhanced through the use of silicone resin which is miscible with the silicone hair conditioning agent. Silicone resins are highly crosslinked polymeric siloxane systems. The crosslinking is introduced through the incorporation of 30       trifunctional and tetrafunctional silanes with monofunctional or difunctional, or both, monomer units during manufacture of the silicone resin. As is well understood in the art, the degree of crosslinking that is required in order to result in a silicone resin will vary according to the specific silane units 35       incorporated into the silicone resin. In general, silicone

materials which have a sufficient level of trifunctional and tetrafunctional siloxane monomer units (and hence, a sufficient level of crosslinking) such that they dry down to a rigid, or hard, film are considered to be silicone resins. The ratio of oxygen atoms to silicon atoms is indicative of the level of crosslinking in a particular silicone material. Silicone resins will generally have at least about 1.1 oxygen atoms per silicon atom. Preferably, the ratio of oxygen: - silicon atoms is at least about 1.2:1.0. Typical silanes used in the manufacture of silicone resins are monomethyl-, dimethyl-, monophenyl-, diphenyl-, methylphenyl-, monovinyl-, and methyl-vinyl-chlorosilanes, and tetrachlorosilane. Preferred resins are the methyl substituted silicone resins, such as those offered by General Electric as GE SS4230 and SS4267. Commercially available silicone resins will generally be supplied in an unhardened form in a low viscosity volatile or nonvolatile silicone fluid. The silicone resins for use herein should be supplied and incorporated into the present compositions in such non-hardened form rather than as a hardened resin, as will be readily apparent to those skilled in the art.

The weight ratio of the nonvolatile silicone fluid conditioning component to the silicone resin component is preferably from about 4:1 to about 400:1. More preferably such ratio is from about 9:1 to about 200:1, most preferably from about 19:1 to about 100:1, particularly when the silicone fluid component is a polydimethylsiloxane fluid or a mixture of polydimethylsiloxane fluid and polydimethylsiloxane gum, as described above.

Other active hair care materials for use with the vehicle systems of the present invention are silicone polymer materials which provide both style retention and conditioning benefits to the hair. These include silicone polymers that are rigid silicone polymers. Such materials are described in U.S. Patent 4,902,499, Bolich et al., issued February 20, 1990, incorporated herein by reference.

Additional cationic conditioning materials may be used in the present compositions. In general, cationic surfactants useful as hair conditioning agents include both quaternary ammonium and amine cationic surfactant materials. If such a material other  
5 than the secondary thickener component is included in the present compositions it will generally be present at levels up to about 2.5%, preferably at from about 0.5% to about 2.0%, by weight of the composition.


Cationic surfactants that can be used, in general, contain  
10 amino or quaternary ammonium hydrophilic moieties which are positively charged when dissolved in the aqueous composition of the present invention. Cationic surfactants among those useful herein are disclosed in the following documents, all incorporated  
15 by reference herein: M.C. Publishing Co., McCutcheon's, Detergents & Emulsifiers, (North American Edition 1979); Schwartz, et al., Surface Active Agents, Their Chemistry and Technology, New York: Interscience Publishers, 1949; U.S. Patent 3,155,591, Hilfer, issued November 3, 1964; U.S. Patent 3,929,678, Laughlin, et al., issued December 30, 1975; U.S. Patent 3,959,461, Bailey,  
20 et al., issued May 25, 1976; and U.S. Patent 4,387,090, Bolich, Jr., issued June 7, 1983.

Specific quaternary ammonium salts include dialkyldimethyl-ammonium chlorides, wherein the alkyl groups have from about 12 to about 22 carbon atoms and are derived from long-chain fatty acids,  
25 such as hydrogenated tallow fatty acid (tallow fatty acids yield quaternary compounds wherein R<sub>1</sub> and R<sub>2</sub> have predominately from 16 to 18 carbon atoms). Examples of quaternary ammonium salts useful in the present invention include ditallowdimethyl ammonium chloride, ditallowdimethyl ammonium methyl sulfate, dihexadecyl  
30 dimethyl ammonium chloride, di(hydrogenated tallow) dimethyl ammonium chloride, dioctadecyl dimethyl ammonium chloride, dieicosyl dimethyl ammonium chloride, didocosyl dimethyl ammonium chloride, di(hydrogenated tallow) dimethyl ammonium acetate, dihexadecyl dimethyl ammonium chloride, dihexadecyl dimethyl  
35 ammonium acetate, ditallow dipropyl ammonium phosphate, ditallow

dimethyl ammonium nitrate, di(coconutalkyl) dimethyl ammonium chloride, and stearyl dimethyl benzyl ammonium chloride. Ditallow dimethyl ammonium chloride, dicetyl dimethyl ammonium chloride, and stearyl dimethyl benzyl ammonium chloride are commonly used quaternary ammonium salts.

Salts of primary, secondary and tertiary fatty amines are also preferred cationic surfactant materials for use herein. The alkyl groups of such amines preferably have from about 12 to about 22 carbon atoms, and may be substituted or unsubstituted. Secondary and tertiary amines are preferred, tertiary amines are particularly preferred. Such amines, useful herein, include stearamido propyl dimethyl amine, diethyl amino ethyl stearamide, dimethyl stearamine, dimethyl soyamine, soyamine, tri(decyl) amine, ethyl stearylamine, ethoxylated (2 moles E.O.) stearylamine, dihydroxyethyl stearylamine, and arachidylbehenylamine. Suitable amine salts include the halogen, acetate, phosphate, nitrate, citrate, lactate and alkyl sulfate salts. Such salts include stearylamine hydrochloride, soyamine chloride, stearylamine formate, N-tallowpropane diamine dichloride and stearamidopropyl dimethylamine citrate. Cationic amine surfactants included among those useful in the present invention are disclosed in U.S. Patent 4,275,055, Nachtigal, et al., issued June 23, 1981, incorporated by reference herein.

A particular category of cationic quaternary ammonium surfactants that can be advantageously incorporated into the present compositions in combination with the above-described essential unsaturated quaternary ammonium surfactants, are water-insoluble materials having the formula, in salt form:



wherein X is a salt-forming anion as previously described,  $a$  is the charge of the anion X, the radicals  $R_1$ ,  $R_2$ ,  $R_3$ , and  $R_4$  independently are  $C_1$ - $C_6$  alkyl,  $C_{20}$ - $C_{22}$  alkyl, or benzyl wherein one of said radicals is  $C_{20}$ - $C_{22}$  alkyl, preferably  $C_{22}$ , from two to three of said radicals are  $C_1$ - $C_6$  alkyl, preferably  $C_1$ - $C_3$ , more preferably methyl, and zero or one of said radicals is benzyl.

The long chain alkyl (i.e. the  $C_{20}$ - $C_{22}$  alkyl) can be either saturated or unsaturated. If it is unsaturated, the surfactant may also fall within the scope of the essential unsaturated quaternary ammonium surfactant thickener described above. If that is the case, it should be included as part of the unsaturated quaternary ammonium surfactant thickener in any assessment of the compositions hereof.

A quaternary ammonium surfactant of Formula III particularly contemplated herein is: dimethyl behenyl benzyl ammonium salt (alternately referred to as behenalkonium salt), available from Witco Chemical Corp. (Memphis, Tennessee, USA) as a chloride salt under the trade name KEMAMINE BQ-2802C. Another particularly contemplated Formula III material is dimethyl arachidyl benzyl ammonium salt.

The quaternary ammonium surfactant of Formula III is generally used at a level of from about 0.02% to about 10.0%, preferably from about 0.05% to about 3.0%, more preferably from about 0.05% to about 2.0%, by weight, of the composition.

Preferred combinations are compositions containing the surfactant of Formula III, especially in saturated form, in combination with the surfactants of Formulas I or II, or a mixture thereof, wherein the Formula I and II component comprises  $C_{14}$ - $C_{18}$  unsaturated alkyls, preferably at a weight ratio of (Formulas I and II):(Formula III) of about 1:1 to about 4:1.

A particularly useful combination of cationic surfactants that can be used comprises a mixture of di(unsaturated)  $C_{16}$ - $C_{18}$  alkyl (preferably tallow) dimethyl ammonium salt (e.g. the chloride salt as commercially available from Sherex Chemicals under the tradename ADOGEN 470)) and dimethyl (saturated or



- 31 -

unsaturated behenyl and/or arachidyl, preferably saturated) benzyl ammonium salt (e.g. the chloride salt, at a weight ratio of about 1:1 at about 4:1, more preferably about 1:1 to about 3:1.

5 These combinations of cationic surfactants can provide improved overall performance for hair styling/conditioning products, especially for as hair rinse products containing a styling/conditioning copolymer. Whereas the unsaturated quaternary ammonium surfactant thickener component, especially the preferred dimethyl, di(C<sub>16</sub>-C<sub>18</sub>) alkyl-substituted surfactants, can provide  
10 products with excellent rheology, hair conditioning, and style hold, style hold can be improved through the use of the long chain C<sub>20</sub>-C<sub>22</sub> alkyl-substituted materials of Formula III while retaining the excellent rheology and conditioning benefits of the unsaturated thickener component.

15 Hydrolyzed animal protein hair conditioning agents may also be included in the present compositions. Such materials are present in the compositions at levels of from about 0.1% to about 1.5%. An example of a commercially available material is sold under the tradename Crotein Q® from Croda, Inc.

20 Fatty alcohols are known hair conditioning agents and may be included in the present compositions. However, as described *supra* such materials tend to deposit on hair and leave hair feeling dirty after use. Hence, it may be described that any fatty alcohol materials included in the compositions of the present  
25 invention be present at levels no greater than about 1%.

Combinations of the aforementioned conditioning agents may also be used in the present compositions.

#### Hair Setting Agent

30 The compositions of the present invention also can contain an effective amount of a hair setting agent to impart styling benefits upon application to hair. The term "hair setting agent" means a hair setting polymer and any carrier or diluent, not including the diluent of the vehicle system described above, that may be used in conjunction with the polymer. As used herein,  
35 "hair styling polymer" means any polymer, natural or synthetic,

that can provide hair setting benefits. Polymers of this type are well known in the art. Generally, the level of hair styling polymer used will be at least about 0.05%, by weight, of the composition. Typically, it will be present at a level of from  
5 about 0.1% to about 10%, preferably from about 0.5% to about 8%.

The hair styling polymers hereof can be homopolymers, copolymers, terpolymers, etc. As used herein, the term "polymer" shall encompass all of such types of polymeric materials. For convenience in describing the polymers hereof, monomeric units  
10 present in the polymers may be referred to as the monomers from which they can be derived. The monomers can be ionic (e.g., anionic, cationic, amphoteric, zwitterionic) or nonionic.

Examples of anionic monomers include:

(i) unsaturated carboxylic acid monomers such as acrylic  
15 acid, methacrylic acid, maleic acid, maleic acid half ester, itaconic acid, fumaric acid, and crotonic acid;

(ii) half esters of an unsaturated polybasic acid anhydride such as succinic anhydride, phthalic anhydride or the like with a hydroxyl group-containing acrylate and/or methacrylate such as  
20 hydroxyethyl acrylate and, hydroxyethyl methacrylate, hydroxypropyl acrylate and the like;

(iii) monomers having a sulfonic acid group such as styrenesulfonic acid, sulfoethyl acrylate and methacrylate, and the like;  
and

(iv) monomers having a phosphoric acid group such as acid  
25 phosphooxyethyl acrylate and methacrylate, 3-chloro-2-acid phosphooxypropyl acrylate and methacrylate, and the like.

Examples of cationic monomers include:

(i) monomers derived from acrylic acid or methacrylic acid,  
30 which is referred to hereinafter collectively as (meth)acrylic acid, and a quaternarized epihalohydrin product of a trialkylamine having 1 to 5 carbon atoms in the alkyl such as (meth)acryloxypropyltrimethylammonium chloride and (meth)acryloxypropyltriethylammonium bromide;

35

- 33 -

(ii) amine derivatives of (meth)acrylic acid or amine derivatives of (meth)acrylamide derived from (meth)acrylic acid or (meth)acrylamide and a dialkylalkanolamine having C<sub>1</sub>-C<sub>4</sub> alkyl groups such as dimethylaminoethyl (meth)acrylate, diethylaminoethyl (meth)acrylate, dimethylaminopropyl (meth)acrylate, or dimethylaminopropyl (meth)acrylamide; and

(iii) derivatives of the products of the group (ii) above by (1) neutralization with an acid such as hydrochloric acid, or lactic acid, (2) modification with a halogenated alkyl, such as methyl chloride, ethyl chloride, methyl bromide, or ethyl iodide, (3) modification with a halogenated fatty acid ester such as ethyl monochloroacetate, or methyl monochloropropionate, and (4) modification with a dialkyl sulfate such as dimethyl sulfate, or diethyl sulfate.

Further cationic unsaturated monomers include amine derivatives of allyl compounds such as diallyldimethylammonium chloride and the like.

The cationic unsaturated monomers can be polymerized in cationic form. As an alternative, they can be polymerized in the form of their nonionic precursors, which are optionally modified to be cationic, for example, by a quaternizing agent (e.g. ethyl monochloroacetate, dimethyl sulfate, etc.).

Examples of the amphoteric monomers include zwitterionized derivatives of the aforementioned amine derivatives of (meth)acrylic acids or the amine derivatives of (meth)acrylamide such as dimethylaminoethyl (meth)acrylate, dimethylaminopropyl(meth)acrylamide by a halogenated fatty acid salt such as potassium monochloroacetate, sodium monobromopropionate, aminomethylpropanol salt of monochloroacetic acid, triethanolamine salts of monochloroacetic acid and the like; and amine derivatives of (meth)acrylic acid or (meth)acrylamide, as discussed above, modified with propanesultone.

These amphoteric monomers, like the aforementioned cationic monomers, can be polymerized in amphoteric form or, as an alternative, they can also be polymerized in the form of their

- 34 -

precursors, which are then optionally converted into the amphoteric state.

Preferred ionic monomers include acrylic acid, methacrylic acid, dimethylaminoethyl methacrylate, quaternized dimethylaminoethyl methacrylate, maleic acid, maleic anhydride half esters, crotonic acid, itaconic acid, diallyldimethyl ammonium chloride, polar vinyl heterocyclics such as vinyl imidazole, vinyl pyridine, styrene sulfonate, and mixtures thereof. Especially preferred ionic monomers include acrylic acid, dimethylaminoethyl methacrylate, quaternized dimethylaminoethyl methacrylate, and mixtures thereof.

The hair setting polymers hereof will generally comprise from 0% to 100% ionic monomers and from 0% to 100% nonionic monomers, preferably from about 2% to about 75% ionic monomers and from about 25% to about 98% nonionic monomers, more preferably from about 5% to about 50% ionic monomers and from about 50% to about 95% nonionic monomers.

Representative examples of low polarity nonionic monomers are acrylic or methacrylic acid esters of  $C_1$ - $C_{24}$  alcohols, such as methanol, ethanol, 1-propanol, 2-propanol, 1-butanol, 2-methyl-1-propanol, 1-pentanol, 2-pentanol, 3-pentanol, 2-methyl-1-butanol, 1-methyl-1-butanol, 3-methyl-1-butanol, 1-methyl-1-pentanol, 2-methyl-1-pentanol, 3-methyl-1-pentanol, t-butanol, cyclohexanol, 2-ethyl-1-butanol, 3-heptanol, benzyl alcohol, 2-octanol, 6-methyl-1-heptanol, 2-ethyl-1-hexanol, 3,5-dimethyl-1-hexanol, 3,5,5-trimethyl-1-hexanol, 1-decanol, 1-dodecanol, 1-hexadecanol, 1-octadecanol, and the like, the alcohols having from about 1-24 carbon atoms with the average number of carbon atoms preferably being from about 4-18, more preferably from about 4-12; styrene; chlorostyrene; vinyl esters such as vinyl acetate; vinyl chloride; vinylidene chloride; acrylonitrile; alpha-methylstyrene; t-butylstyrene; butadiene; cyclohexadiene; ethylene; propylene; vinyl toluene; alkoxyalkyl (meth)acrylate, such as methoxy ethyl (meth)acrylate, butoxyethyl (meth)acrylate; and mixtures thereof. Other nonionic monomers include acrylate and methacrylate derivatives

such as allyl acrylate and methacrylate, cyclohexyl acrylate and methacrylate, and methacrylate, oleyl acrylate and methacrylate, benzyl acrylate and methacrylate, tetrahydrofurfuryl acrylate and methacrylate, ethylene glycol di-acrylate and -methacrylate, 5 1,3-butyleneglycol di-acrylate and -methacrylate, diacetoneacrylamide, isobornyl (meth)acrylate, and the like.

Preferred nonionic monomers include n-butyl methacrylate, isobutyl methacrylate, 2-ethylhexyl methacrylate, methyl methacrylate, t-butylacrylate, t-butylmethacrylate, and mixtures 10 thereof.

Representative polar nonionic monomers include acrylamide, N,N-dimethylacrylamide, methacrylamide, N-t-butyl acrylamide, methacrylonitrile, acrylate, and methacrylate alcohols (e.g. C<sub>2</sub>-C<sub>8</sub> 15 acrylate and methacrylate alcohols such as hydroxyethyl acrylate, hydroxypropyl acrylate, hydroxyethyl methacrylate, and hydroxypropyl methacrylate), vinyl pyrrolidone, vinyl ethers, such as methyl vinyl ether, acyl lactones, vinyl pyridine, allyl alcohols, vinyl alcohols and vinyl caprolactam.

Examples of anionic hair styling polymers are copolymers of 20 vinyl acetate and crotonic acid, terpolymers of vinyl acetate, crotonic acid and a vinyl ester of an alpha-branched saturated aliphatic monocarboxylic acid such as vinyl neodecanoate; and copolymers of methyl vinyl ether and maleic anhydride (molar ratio about 1:1) wherein such copolymers are 50% esterified with a 25 saturated aliphatic alcohol containing from 1 to 4 carbon atoms such as ethanol or butanol; and acrylic copolymers and terpolymers containing acrylic acid or methacrylic acid as the anionic radical containing moiety such as copolymers with methacrylic acid, butyl acrylate, ethyl methacrylate, etc. Another example of an acrylic 30 polymer which can be employed in the compositions of the present invention is a polymer of tertiary-butyl acrylamide, acrylic acid, and ethyl acrylate.

An example of an amphoteric polymer which can be used in the present invention is Octylacrylamide/Acrylates/Butylaminoethyl 35 Methacrylate Copolymer, described generally in U.S. Pat. No.

4,192,861 as being a polymer of N-tert-octyl acrylamide, methyl methacrylate, hydroxypropyl methacrylate, acrylic acid and t-butyl aminoethyl methacrylate, of appropriate molecular weight for purposes hereof.

5        Examples of cationic hair styling polymers are copolymers of amino-functional acrylate monomers such as lower alkylamino alkyl acrylate or methacrylate monomers such as dimethyl aminoethyl-methacrylate with compatible monomers such as N-vinylpyrrolidone or alkyl methacrylates such as methyl methacrylate and ethyl  
10       methacrylate and alkyl acrylates such as methyl acrylate and butyl acrylate. Cationic polymers containing N-vinylpyrrolidone are commercially available from GAF Corp.

      Still other organic, hair styling polymers include carboxy-methyl cellulose, copolymers of PVA and crotonic acid, copolymers  
15       of PVA and maleic anhydride, sodium polystyrene sulfonate, PVP/ethylmethacrylate/methacrylic acid terpolymer, vinyl acetate/crotonic acid/vinyl neodecanoate copolymer, octylacrylamide/acrylates copolymer, monoethyl ester of poly(methyl vinyl ether-maleic acid), and octylacrylamide/acrylate/butylaminoethyl methacrylate  
20       copolymers. Mixtures of polymers may also be used.

      Highly preferred active hair care materials for use with the vehicle systems of the present invention are hair holding/styling polymers. Any of the silicone-containing hair styling polymers known in the art for this purpose can be used.

25       In its broadest sense, the silicone-containing polymers useful in the compositions of the present invention include all copolymers of silicone with a non-silicone adhesive polymer which:  
      (a) when dried, the copolymer phase-separates into a discontinuous phase which includes the silicone portion and a continuous phase  
30       which includes the non-silicone portion; and (b) the silicone portion is covalently attached to the non-silicone portion. The silicone-containing polymers hereof are such that when formulated into the finished hair care composition, when dried, the polymer phase separates into a discontinuous phase which includes the  
35       polydimethylsiloxane macromer and a continuous phase which

- 37 -

includes the backbone. The phase-separating nature of the compositions of the present invention may be determined as follows:

5 The polymer is cast as a solid film out of a good solvent (i.e., a solvent which dissolves both the backbone and the sil-  
cone). This film is then sectioned and examined by transmission  
electron micrography. Microphase separation is demonstrated by  
the observation of inclusions in the continuous phase. These  
10 inclusions should have the proper size to match the size of the  
silicone chain (typically a few hundred nm or less) and the proper  
density to match the amount of silicone present. This behavior is  
well documented in the literature for polymers with this structure  
(see, for example, S. D. Smith, Ph.D. Thesis, University of  
Virginia, 1987, and references cited therein).

15 A second method for determining phase-separating character-  
istics involves examining the enrichment of the concentration of  
silicone at the surface of a polymer film relative to the concen-  
tration in the bulk polymer. Since the silicone prefers the low  
energy air interface, it preferentially orients on the polymer  
20 surface. This produces a surface which is entirely covered by  
silicone even when the concentration of the silicone by weight in  
the whole polymner is low (2% to 20%). This is demonstrated  
experimentally by ESCA (electron spectroscopy for chemical analy-  
sis) of the dried film surface. Such an analysis shows a high  
25 level of silicone and a greatly reduced level of backbone polymer  
when the film surface is analyzed. (Surface here means the first  
few tens of Angstroms of film thickness.) By varying the angle of  
the interrogating beam the surface can be analyzed to varying  
depths.

30 The most preferred silicone-containing polymers comprise a  
vinyl polymeric backbone, preferably having a Tg or a Tm above  
about -20°C and, grafted to the backbone, a polydimethylsiloxane  
macromer having a weight average molecular weight of from about  
1,000 to about 50,000, preferably from about 5,000 to about  
35 40,000, most preferably about 10,000 to about 20,000. As used

- 38 -

herein, the abbreviation "Tg" refers to the glass transition temperature of the non-silicone backbone, and the abbreviation "Tm" refers to the crystalline melting point of the non-silicone backbone, if such a transition exists for a given polymer.

5           Highly preferred examples of such materials are the silicone-containing copolymers as described in the following patent applications: Serial Number 07/758,319, Torgerson, Bolich and Garbe, filed August 27, 1991; and Serial Number 07/758,320, Bolich and Torgerson, filed August 27, 1991; both of which are  
10           incorporated by reference herein, and in European Patent Application 90307528.1, Hayama et al. (Publication No. 0 408 311, January 16, 1991). Such polymers typically have a weight average molecular weight of at least about 10,000, generally from about 75,000 to about 3,000,000, and also preferably, have a Tg of at  
15           least about -20°C.

          In addition to the graft copolymers described above, useful copolymers include block copolymers containing up to about 50% (preferably from about 10% to about 20%) by weight of one or more polydimethyl siloxane blocks and one or more non-silicone blocks  
20           (preferably acrylates or vinyls).

          Preferred polymers comprise a vinyl polymeric backbone having a Tg or a Tm above about -20°C and, grafted to the backbone, a polydimethylsiloxane macromer having a weight average molecular weight of from about 1,000 to about 50,000, preferably from about  
25           5,000 to about 40,000, most preferably about 20,000.

          The silicone-containing polymers utilized as styling/conditioning agents generally comprise C monomers together with monomers selected from the group consisting of A monomers, B monomers, and mixtures thereof, as described in more detail below. These  
30           copolymers contain at least A or B monomers together with C monomers, and preferred copolymers contain A, B and C monomers.

          Examples of useful copolymers and how they are made are described in detail in U.S. Patent 4,693,935, Mazurek, issued September 15, 1987, and U.S. Patent 4,728,571, Clemens et al.,  
35           issued March 1, 1988, both of which are incorporated herein by



- 39 -

reference. These copolymers are comprised of monomers A, C and, optionally, B, which are defined as follows. A, when used, is at least one free radically polymerizable monomer or monomers. B, when used, comprises at least one monomer copolymerizable with A and is selected from the group consisting of polar (relative to A) monomers and macromers having a T<sub>g</sub> or a T<sub>m</sub> above about -20°C. When used, B may be up to about 98%, preferably up to about 80%, more preferably up to about 20%, of the total monomers in the copolymer. Polar monomers include ionic monomers as well as polar nonionic monomers. Monomer C comprises from about 0.01% to about 50.0% of the total monomers in the copolymer.

Representative examples of A monomers are acrylic or methacrylic acid esters of C<sub>1</sub>-C<sub>18</sub> alcohols, such as methanol, ethanol, 1-propanol, 2-propanol, 1-butanol, 2-methyl-1-propanol, 1-pentanol, 2-pentanol, 3-pentanol, 2-methyl-1-butanol, 1-methyl-1-butanol, 3-methyl-1-butanol, 1-methyl-1-pentanol, 2-methyl-1-pentanol, 3-methyl-1-pentanol, t-butanol, cyclohexanol, 2-ethyl-1-butanol, 3-heptanol, benzyl alcohol, 2-octanol, 6-methyl-1-heptanol, 2-ethyl-1-hexanol, 3,5-dimethyl-1-hexanol, 3,5,5-trimethyl-1-hexanol, 1-decanol, 1-dodecanol, 1-hexadecanol, 1-octadecanol, and the like, the alcohols having from about 1-18 carbon atoms with the average number of carbon atoms being from about 4-12; styrene; vinyl acetate; vinyl chloride; vinylidene chloride; acrylonitrile; alpha-methylstyrene; t-butylstyrene; butadiene; cyclohexadiene; ethylene; propylene; vinyl toluene; and mixtures thereof. Preferred A monomers include n-butyl methacrylate, isobutyl methacrylate, 2-ethylhexyl methacrylate, methyl methacrylate, t-butylacrylate, t-butylmethacrylate, and mixtures thereof.

Representative examples of B monomers include acrylic acid, methacrylic acid, N,N-dimethylacrylamide, dimethylaminoethyl methacrylate, quaternized dimethylaminoethyl methacrylate, methacrylonitrile, polystyrene macromer, methacrylamide, maleic anhydride and its half esters, itaconic acid, acrylamide, acrylate alcohols, hydroxyethyl methacrylate, diallyldimethyl ammonium


- 40 -

chloride, vinyl pyrrolidone, vinyl ethers (such as methyl vinyl ether), maleimides, acylactones, vinyl pyridine, vinyl imidazole, other polar vinyl heterocyclics, styrene sulfonate, and mixtures thereof. Preferred B monomers include acrylic acid, N,N-dimethyl-  
 5 acrylamide, dimethylaminoethyl methacrylate, quaternized dimethylaminoethyl methacrylate, vinyl pyrrolidone, and mixtures thereof. Additional suitable A and B monomers are described above in the discussion of non-silicone-containing polymers.


The C monomer has the general formula:




wherein X is a vinyl group copolymerizable with the A and B monomers; Y is a divalent linking group; R is a hydrogen, lower alkyl, aryl or alkoxy; Z is a monovalent siloxane polymeric moiety having a number average molecular weight of at least about 500, is  
 15 essentially unreactive under copolymerization conditions and is pendant from the vinyl polymeric backbone, described above; n is 0 or 1; and m is an integer from 1 to 3. C has a weight average molecular weight of from about 1,000 to about 50,000, preferably from about 5,000 to about 40,000, most preferably from about  
 20 10,000 to about 20,000. Preferably, the C monomer has the formula:



In those structures, m is 1, 2 or 3 (preferably m = 1); p is  
 25 0 or 1; R<sup>4</sup> is alkyl or hydrogen; q is an integer from 2 to 6; s is an integer from 0 to 2; X is



R<sup>1</sup> is hydrogen or -COOH (preferably R<sup>1</sup> is hydrogen); R<sup>2</sup> is hydro-  
 30 gen, methyl or -CH<sub>2</sub>COOH (preferably R<sup>2</sup> is methyl); Z is



35

- 41 -

R<sup>4</sup> is alkyl, alkoxy, alkylamino, aryl, or hydroxyl (preferably R<sup>4</sup> is alkyl); and r is an integer from about 5 to about 700 (preferably r is about 130 to about 250). Particularly preferred is when p=0 and q=3.

5       The preferred polymers useful in the present invention generally comprise from 0% to about 98% (preferably from about 5% to about 98%, more preferably from about 50% to about 90%) of monomer A, from 0% to about 98% (preferably from about 7.5% to about 80%) of monomer B, and from about 0.1% to about 50% (preferably from about 0.5% to about 40%, most preferably from about 2% to about 25%) of monomer C. The combination of the A and B monomers preferably comprises from about 50.0% to about 99.9% (more preferably about 60% to about 99%, most preferably from about 75% to about 95%) of the polymer. The composition of any particular copolymer will help determine its formulational properties. For example, polymers which are soluble in an aqueous formulation preferably have the composition: from 0% to about 70% (preferably from about 5% to about 70%) monomer A, from about 30% to about 98% (preferably from about 3% to about 80%) monomer B, and from about 1% to about 40% monomer C. Polymers which are dispersible have the preferred composition: from 0% to about 70% (more preferably from about 5% to about 70%) monomer A, from about 20% to about 80% (more preferably from about 20% to about 60%) monomer B, and from about 1% to about 40% monomer C.

25       Polymers for use in the present invention include the following (the weight percents below refer to the amount of reactants added in the polymerization reaction, not necessarily the amount in the finished polymer):

30       acrylic acid/n-butylmethacrylate/polydimethylsiloxane (PDMS) macromer-20,000 molecular weight (e.g., 10/70/20 w/w/w) (I)

N,N-dimethylacrylamide/isobutyl methacrylate/PDMS macromer - 20,000 molecular weight (e.g., 20/60/20 w/w/w) (II)

35

- 42 -

dimethylaminoethyl methacrylate/isobutyl methacrylate/2-ethylhexyl-methacrylate/PDMS macromer-20,000 molecular weight (e.g., 25/40/15/20 w/w/w/w) (III)  
dimethylacrylamide/PDMS macromer-20,000 molecular weight (e.g., 80/20 w/w) (IV)

t-butylacrylate/t-butylmethacrylate/PDMS macromer-10,000 molecular weight (e.g., 56/24/20 w/w/w) (V)

t-butylacrylate/PDMS macromer-10,000 molecular weight (e.g., 80/20 w/w) (VI)

t-butylacrylate/N,N - dimethylacrylamide/PDMS macromer-10,000 molecular weight (e.g., 70/10/20 w/w/w) (VII)

t-butylacrylate/acrylic acid/PDMS macromer-10,000 molecular weight (e.g., 75/5/20 w/w/w) (VIII).

The particle size of the hair setting agent of the present compositions may have some effect on performance in product. This, of course, will vary from polymer to polymer and from product to product.

The hair setting polymers are preferably provided in a solvent for the polymer, generally prior to combination with the vehicle systems of the present invention.

The solvent selected must be able to dissolve or disperse the particular hair styling polymer being used. Suitable solvents for use in the present invention, in general, include, but are not limited to, alkyl alcohols (such as linalool and decyl alcohol), hydrocarbons (such as isobutane, hexane, decane, dodecane, and tridecane), hydrocarbon esters (such as C<sub>8</sub>-C<sub>12</sub> alkanoates, e.g. methyl decanoate, di (C<sub>2</sub>-C<sub>3</sub>) alkyl adipates, e.g. diisopropyl adipate, C<sub>6</sub>-C<sub>10</sub> alkyl acetates, e.g. octyl acetate, and benzoates, e.g. butyl benzoate,), volatile silicon derivatives, especially siloxanes (such as phenyl pentamethyl disiloxane, phenethyl

- 43 -

pentamethyl disiloxane, methoxypropyl heptamethyl cyclotetra-  
siloxane, chloropropyl pentamethyl disiloxane, hydroxypropyl  
pentamethyl disiloxane, octamethyl cyclotetrasiloxane, decamethyl  
cyclopentasiloxane), ethers, such as di (C<sub>3</sub>-C<sub>7</sub>) alkylethers, and  
5 mixtures thereof. Preferred solvents include volatile silicone  
fluids, and mixtures of silicone fluids with ester, ether, and or  
hydrocarbon solvents. The choice of solvent will depend upon the  
particular hair setting polymer chosen and the diluent utilized  
for the vehicle system, as described above. In general, it is  
10 preferred that the hair setting polymer solvent be dispersible,  
but immiscible, with the vehicle system diluent. Also, the hair  
setting polymer solvent is preferably volatile and not soluble in  
water. For purposes hereof, "volatile" means a boiling point, at  
atmospheric pressure, of less than about 300°C, preferably from  
15 about 100°C to about 300°C, and "not soluble in water" means a  
water solubility in water at 25°C of 0.2% or less, preferably  
about 0.1% or less, on a water plus solvent weight basis.

The performance of the styling polymers can be improved  
through the incorporation of a nonvolatile plasticizer into the  
20 styling polymer-solvent solution. The preferred solvents in these  
systems are volatile silicone fluids in which the styling polymer  
is soluble or dispersible. The plasticizer will generally be  
present in the compositions at a plasticizer: styling polymer  
weight ratio of about 1:20: to about 1:1, preferably from about  
25 1:15 to about 1:2, more preferably from about 1:12 to about 1:2.5.  
As used herein, "nonvolatile" in regard to plasticizers means that  
the plasticizer exhibits essentially no vapor pressure at atmos-  
pheric pressure and 25°C. The polymer-volatile solvent solution  
should not suffer from substantial plasticizer weight loss while  
30 the volatile solvent is evaporating, since this would reduce  
plasticization of the styling polymer during use. The plasti-  
cizers for use herein should generally have boiling points of  
about 250°C or higher. Such plasticizers are nonvolatile for  
purposes hereof.

35

- 44 -

The plasticizer should also be compatible with the hair styling polymer-volatile solvent solution. By "compatible" with respect to the plasticizer and the polymer-volatile solvent solution, it is meant that the plasticizer does not adversely interact with the hair styling/conditioning copolymer, and must be miscible in said solution. In general, the nonvolatile plasticizers for use herein will be of relatively low water solubility. The solubility parameter of these plasticizers will generally be between about 7 and about 10, preferably between about 8 and about 9 (units equal  $(\text{cal/cc})^{1/2}$ ). The solubility parameter is defined in the Polymer Handbook 3rd Ed. (John Wiley and Sons, New York), J. Brankrup and E.H. Immergut, Chapter VII, pp. 519-559, as the square root of the cohesive energy density and describes the attractive strength between molecules of the material. Solubility parameters may be determined by direct measurement, correlations with other physical properties, or indirect calculation as set forth by Immergut.

Plasticizers are well known in the art and are generally described in Kirk-Othmer Encyclopedia of Chemical Technology, second edition, Volume 15, pp. 720-789. (John Wiley & Sons, Inc. New York, 1968) under the topic heading "Plasticizers", and by J. Kern Sears and Joseph R. Darby in the text The Technology of Plasticizers (John Wiley & Sons, Inc., New York, 1982), both incorporated herein by reference. See especially in the Appendix of Sears/Darby Table A.9 at pages 983-1063 where a wide variety of plasticizers are disclosed.

The plasticizers for use herein include both cyclic and acyclic nonvolatile materials. Suitable categories of nonvolatile plasticizers include adipates, phthalates, isophthalates, azelates, stearates, citrates, trimellitates, silicone copolyols iso  $\text{C}_{14}$ - $\text{C}_{22}$  alcohols, methyl alkyl silicones, carbonates, sebacates, isobutyrates, oleates, phosphates, myristates, ricinoleates, pelargonates, valerates, oleates, camphor, and castor oil, and silicone copolyols.

- 45 -

Examples of adipate plasticizers include adipic acid derivatives such as diisobutyl adipate, bis(2-ethylhexyl) adipate, diisodecyl adipate, bis(2-butoxyethyl) adipate, and di-n-hexyl adipate.

5        Examples of phthalate plasticizers include phthalic acid derivatives such as dibutyl phthalate, butyl octyl phthalate, di-n-octyl phthalate, diisooctyl phthalate, bis(2-ethylhexyl) phthalate, n-octyl n-decyl phthalate, di-n-hexyl phthalate, isooctyl isodecyl phthalate, diisodecyl phthalate, ditridecyl  
10       phthalate, butyl cyclohexyl phthalate, diisooctyl benzyl phthalate, butyl benzyl phthalate, dicyclohexyl phthalate, diphenyl phthalate, isodecyl benzyl phthalate, and bis(2-butoxyethyl) phthalate.

Isophthalate plasticizers include bis(2-ethylhexyl) isophthalate, and diisooctyl benzyl phthalate.

15       Examples of azelate plasticizers include azelaic acid derivatives such as di(2-ethylhexyl) azelate, and bis(2-ethylhexyl) azelate.

Examples of stearate plasticizers include stearic acid derivatives such as n-butyl stearate, butyl acetoxystearate, and  
20       butoxyethyl stearate.

Examples of citrate plasticizers include citric acid derivatives such as acetyl tri-n-butyl citrate, tri-n-butyl citrate, and acetal tri-2-ethyl hexyl citrate.

25       Examples of trimellitate plasticizers include tri-(2-ethylhexyl) trimellitate, and triisooctyl trimellitate.


Other examples of plasticizers include dibutyl carbonate, butyl oleate, n-butyl, butyrate, isobutyl butyrate, isopropyl butyrate, dibutyl carbonate, ethyl palmitate, isooctyl palmitate, methyl ricinoleate, butyl ricinoleate, diisooctyl sebacate,  
30       triisobutyl phosphate, isodecyl pelargonate, ethyl valerate, isocetyl alcohol, octododecanol, isopropyl myristate, isostearyl alcohol and methyl alkyl silicones having C<sub>2</sub>-C<sub>20</sub> alkyl and from 1 to about 500 siloxane monomer units.

35       Silicone copolyols, described *supra*, can also be used as plasticizers.

- 46 -

If a plasticizer is used, the molecular weight, weight average, of the styling polymer is preferably at least about 200,000, more preferably from about 300,000 to about 800,000, most preferably from about 400,000 to about 600,000.

- 5 Other preferred cationic quaternary ammonium surfactants for inclusion in the compositions hereof, as a supplemental cationic conditioning agent, are mono-long chain, tri-short chain ammonium quaternary surfactants. Suitable surfactants of this category are those having the formula, in salt form:



- 15 wherein X is a salt-forming anion as previously described, a is the charge of the anion X, R<sub>1</sub> is a C<sub>14</sub>-C<sub>22</sub> alkyl or C<sub>14</sub>-C<sub>22</sub> alkyl amido C<sub>2</sub>-C<sub>6</sub> alkylene, preferably C<sub>16</sub>-C<sub>22</sub>, and R<sub>2</sub>, R<sub>3</sub>, and R<sub>4</sub> independently are C<sub>1</sub>-C<sub>6</sub> alkyl, or benzyl, preferably C<sub>1</sub>-C<sub>3</sub> or benzyl, more preferably methyl or benzyl, wherein only one of the  
20 short chain radicals is benzyl. The long chain radical can be either saturated or unsaturated. The Formula IV surfactant utilized preferably is more water-soluble than the quaternary surfactants of Formulas I and II that are present in the composition.

- 25 These cationic surfactants are particularly useful for improving wet feel of the compositions in formulations also containing a distributing aid. In particular, they are advantageously utilized in compositions containing hair styling agents, or other tacky materials, which require a distributing aid  
30 for adequate distribution of the hair setting agent or other tacky additive.

- Preferred surfactants of Formula (IV) include C<sub>14</sub>-C<sub>22</sub> alkyl (saturated or unsaturated) dimethyl benzyl ammonium chlorides such as stearyl benzyl dimethyl ammonium chloride, and C<sub>14</sub>-C<sub>22</sub> alkyl  
35 (saturated or unsaturated) trimethyl ammonium chlorides.



- 47 -

Surfactants of Formula (IV) are generally used at levels of from about 0.05% to about 1.0% by weight of the composition, preferably from about 0.1% to about 0.75%, more preferably from about 0.1% to about 0.4%. Also, preferably, the ratio of formula I plus II surfactants to Formula IV surfactants is from about 1:20 to about 20:1, more preferably from about 1:1 to about 15:1, more preferably from about 2:1 to about 10:1.

These additional active cosmetic materials are generally present at a total level of from about 0% to about 20%, preferably from about 0.1% to about 20%, by weight of the cosmetic composition. For purposes hereof, these additional active cosmetic components shall not include the unsaturated quaternary ammonium surfactants which are encompassed by Formulas I and II, even though such surfactants generally will have cosmetic efficacy, eg. as hair or skin conditioners. The 0% level reflects the situation when one of the vehicle component provides the hair care activity to the present compositions. For example, if the vehicle system comprises a water-insoluble quaternary ammonium compound, this material will provide hair conditioning benefits as well. The level of the active cosmetic care material varies depending upon which active material is chosen, the particular cosmetic compositions to be formulated therewith, and the level of benefit desired.

Other optional components that can be added to the cosmetic compositions of the present invention do not provide any direct cosmetic care benefit but instead enhance the composition in some way. Examples of such materials are coloring agents, such as any of the FD&C or D&C dyes; opacifiers, pearlescent aids, such as ethylene glycol distearate or TiO<sub>2</sub> coated mica; pH modifiers, such as citric acid, succinic acid, phosphoric acid, sodium hydroxide, and sodium carbonate; perservatives, such as benzyl alcohol, ethyl paraben, propyl paraben, and imidazolidonyl urea; and antioxidants. Such agents generally are used individually at a level of from about 0.001% to about 10%, preferably from about 0.01% to about 5%, of the hair care composition.

- 48 -

The vehicle systems and cosmetic compositions of the present invention can be made using conventional formulation and mixing techniques. In one procedure for manufacture, a silicone conditioner, quaternary ammonium surfactant, and at least a portion of the solvent component are premixed prior to the addition of the remaining components. Methods of making various types of cosmetic compositions are described more specifically in the following examples.

The following examples illustrate the present invention. It will be appreciated that other modifications of the present invention within the skill of those in the cosmetic composition formulation art can be undertaken without departing from the spirit and scope of this invention.

All parts, percentages, and ratios herein are by weight unless otherwise specified.

#### Example I

The following is a hair styling rinse composition representative of the present invention.

	<u>Component</u>	<u>Weight %</u>
20	<u>Styling Agent Premix</u>	
	Silicone Copolymer <sup>1</sup>	2.00
	Phenylpentamethyl disiloxane	9.00
	<u>Xanthan Premix</u>	
	Xanthan gum	0.25
25	DRO H <sub>2</sub> O	25.00
	<u>Main Mix</u>	
	Dioleyl-dimethylammonium chloride (DODMAC)	0.50
	EDTA, disodium salt	0.10
30	D.C. 929 <sup>2</sup>	2.00
	Perfume	0.10
	Natrosol Plus CS Grade D-67 <sup>3</sup>	0.75
	Locust bean gum	0.75
	Kathon CG <sup>4</sup>	0.04
35	DRO H <sub>2</sub> O	q.s. to 100%

- 49 -

- 1 20/60/20 N,N-dimethylacrylamide/isobutyl methacrylate/PDMS  
macromer (20,000 MW), polymer molecular weight about 300,000.
- 2 Amodimethicone, commercially available from Dow Corning
- 3 Hydrophobically modified hydroxyethylcellulose having a C<sub>18</sub>  
5 alkyl substitution of from about 0.50% to about 0.95%, by  
weight, and a hydroxyethyl molar substitution of from about 2.3  
to about 3.3, and where the average molecular weight of the  
hydroxyethyl cellulose prior to substitution is approximately  
700,000, available from Aqualon Company.
- 10 4 preservative commercially available from Rohm and Haas  
The composition is prepared as follows. The DRO (double  
reverse osmosis) water is first heated to 71°F. The DODMAC, EDTA,  
and D.C. 929 are added to the water and mixed for about 5 minutes.  
The Natrosol is added to the composition with mixing. The Locust  
15 Bean Gum is added to the composition with mixing. The composition  
is then homogenized with a disperser, for example a Gifford-Wood  
mill, for about 2 minutes. The batch is then cooled to 38°F. The  
xanthan gum premix, styling agent premix, perfume and Kathan CG  
are added to the composition with mixing for about 10 minutes.  
20 The batch is cooled to ambient temperature and stored.

Example II

The following is a hair styling rinse composition representa-  
tive of the present invention.

	<u>Component</u>	<u>Weight %</u>
25	<u>Styling Agent Premix</u>	
	Silicone Copolymer <sup>1</sup>	3.00
	Phenylpentamethyl disiloxane	9.00
	Hydroxypropylpentamethyl disiloxane	6.00
	<u>Silicone Gum Premix</u>	
30	Silicone Gum G.E. SE 76 <sup>2</sup>	0.50
	Decamethyl cyclopentasiloxane	4.00
	<u>Main Mix</u>	
	Natrosol Plus CS Grade D-67 <sup>3</sup>	0.60
	Locust bean gum	0.50
35	EDTA, disodium salt	0.15

- 50 -

	ADOGEN 470 <sup>3</sup>	0.65
	Glydant <sup>4</sup>	0.40
	Perfume	0.20
	DRO H <sub>2</sub> O	q.s. to 100%
5	1 10/70/20 acrylic acid/n-butyl methacrylate/silicone macromer, the macromer having a molecular weight of about 20,000, prepared in a manner similar to Example C-2c of U.S. Patent 4,728,571, Clemens, issued March 1, 1988, polymer molecular weight about 300,000	
10	2 Commercially available from General Electric	
	3 hydrophobically-modified hydroxyethyl cellulose commercially available from Aqualon Co.	
	4 preservative commercially available from Glyco, Inc.	
15	5 Partially hydrogenated ditallow dimethyl ammonium chloride, commercially available from Sherex Chemical Company, Dublin, Ohio, USA.	

The composition is prepared as follows. The DRO water is heated to 71°F. The ADOGEN 470, EDTA, and silicone gum premix are added to the water with mixing for about 5 minutes. The Natrosol is added with mixing. The Locust Bean Gum is added with mixing. The composition is then homogenized with a disperser, for example a Gifford-Wood mill, for about 2 minutes. The batch is cooled to 38°F and the styling agent premix, the perfume and the Glydant are added with mixing for about 10 minutes. The batch is cooled to ambient temperature and stored.

#### Example III

The following is a hair styling rinse composition representative of the present invention.

	<u>Component</u>	<u>Weight %</u>
30	Natrosol Plus CS Grade D-67 <sup>1</sup>	1.20
	Xanthan Gum	0.25
	Citric Acid	0.073
	Sodium Citrate	0.175
	Kathon CG	0.033
35	ADOGEN 470 <sup>3</sup>	0.75

- 51 -

	Hydrogenated Tallow Betaine	0.33
	<u>Styling Agent Premix</u>	
	T-Butyl Acrylate/PDMS Copolymer	
	(10,000 MW - 80/20 W/W)	2.50
5	Phenethyl Pentamethyl Disiloxane	1.875
	D4 Cyclomethicone	5.625
	<u>Silicone Premix</u>	
	Polydimethyl Siloxane Gum/	
	D5 Cyclomethicone (15/85) <sup>2</sup>	2.333
10	Perfume	q.s.
	DRO Water	q.s. to 100%
	<sup>1</sup> Hydrophobically modified hydroxyethyl cellulose available from Aqualon Corp.	
	<sup>2</sup> G.E. SE-76 gum available from G. E. Silicones	
15	<sup>3</sup> Partially hydrogenated ditallow dimethyl ammonium chloride, commercially available from Sherex Chemical Company, Dublin, Ohio, USA	
	The composition is prepared as follows. The xanthan gum is first slurried in water at 4% xanthan gum, until fully hydrated.	
20	In a separate vessel the copolymer is mixed into the phenethyl pentamethyl disiloxane and D4 cyclomethicone.	
	The remaining water is preheated to about 71°C. The ADOGEN 470, citric acid, sodium citrate, and hydrogenated tallow betaine are added to the water and mixed until melted. This mixture is	
25	then cooled to about 65°C. The Natrosol Plus, silicone gum premix, Kathon and perfume are added and mixed until homogeneous. This mixture is then cooled to about 38°C. The xanthan gum premix and copolymer premix are then added and the mixture is agitated until homogeneous. The resulting composition is cooled to ambient	
30	temperature.	

Example IV

The following is a hair conditioning rinse composition which is representative of the present invention.

	<u>Component</u>	<u>Wt. %</u>
35	<u>Silicone Gum Premix</u>	

- 52 -

Octamethyl Cyclotetrasiloxane	3.00
G.E. SE 76 <sup>2</sup>	0.50

Main Mix

5	Natrosol Plus CS Grade D-67 <sup>1</sup>	1.25
	D1 rapeseed alkyl dimethyl ammonium chloride (DRaDMAC)	0.75
	Stearamide DEA	0.10
	Kathon CG	0.04
	DRO Water and fragrance	q.s.to 100%

10

<sup>1</sup> Hydrophobically modified hydroxethylcellulose available from Aqualon

<sup>2</sup> Silicone gum available from General Electric

15 The composition is prepared as follows. The DRO water is first heated to 71°C. The DRaDMAC, stearamide DEA, Natrosol, and the Silicone gum premix are added with mixing. The composition is then homogenized with a disperser, e.g., a Gifford-Wood mill, for about 2 minutes. The composition is cooled to 38°C and the Kathon and perfume are added with mixing for about 10 minutes. The batch

20 is cooled to ambient temperature and stored.

Example V

The following is a hair styling conditioner composition which is representative of the present invention.

	<u>Component</u>	<u>Wt. %</u>
25	Disodium EDTA	0.15
	Monosodium Phosphate	0.04
	Disodium Phosphate	0.12
	ADGEN 470 <sup>4</sup>	0.75
	Locust Bean Gum	0.70
30	Natrosol Plus CS Grade D-67 <sup>1</sup>	0.70
	Glydant	0.37
	Xanthan Gum	0.25
	Perfume	0.02
	Water	q.s.to 100%
35	<u>Silicone Gum Premix</u>	

- 53 -

	G. E. S E 76 <sup>2</sup>	0.50
	Octamethyl Cyclotetrasiloxane	3.00
	<u>Styling Polymer Premix</u>	
	Styling Polymer <sup>3</sup>	3.00
5	Phenyl Pentamethyl Disiloxane	9.00
	Hydroxypropyl Pentamethyl Disiloxane	6.00
	<sup>1</sup> Hydrophobically modified hydroxyethylcellulose available from Aqualon	
	<sup>2</sup> Silicone Gum available from General Electric	
10	<sup>3</sup> Isobutylmethacrylate/2-ethylhexylmethacrylate/N,N-dimethyl-acrylamide copolymer 80/5/15	
	<sup>4</sup> Partially hydrogenated ditallow dimethyl ammonium chloride, commercially available from Sherex Chemical Company, Dublin, Ohio, USA.	
15	The composition is prepared as follows. The DRO water is heated to 71°C. The ADOGEN 470, disodium EDTA, monosodium phosphate, and disodium phosphate are added and the composition is mixed for about 5 minutes. The silicone gum premix, locust bean gum, and Natrosol are added with mixing. The composition is then	
20	homogenized using a disperser, e.g., a Gifford-Wood Mill, for about 2 minutes. The batch is cooled to 38°F and the Xanthan Gum premix, styling polymer premix, perfume and Glydant are added and mixed for about 10 minutes. The composition is then cooled to ambient temperature and stored.	

25

Example VI

The following is a styling rinse composition representative of the present invention.

	<u>Component</u>	<u>Wt. %</u>
	<u>Styling Agent</u>	
30	Silicone Copolymer <sup>1</sup>	3.00
	Octamethyl cyclotetrasiloxane	9.00
	<u>Premix</u>	
	Silicone Gum GE SE76 <sup>2</sup>	0.50
	Decamethyl cyclopentasiloxane	4.00
35	<u>Main Mix</u>	

- 54 -

	Natrosol Plus CS Grade D-67 <sup>3</sup>	1.25
	ADOGEN 470 <sup>5</sup>	0.80
	KEMAMINE Q-1902C <sup>6</sup>	0.40
	Kathon CG <sup>4</sup>	0.03
5	Imidazole	0.15
	Perfume	0.10
	DRO H <sub>2</sub> O	q.s. to 100%
10	<sup>1</sup> 80/20 t-butyacrylate/PDMS macromer, the macromer having a molecular weight of about 10,000, prepared in a manner similar to Example C-2b of U.S. Patent 4,728,571, Clemens issued March 1, 1988.	
	<sup>2</sup> Commercially available from General Electric	
	<sup>3</sup> hydrophobically-modified hydroxyethyl cellulose commercially available from Aqualon Co.	
15	<sup>4</sup> preservative commercially available from Rohm & Haas	
	<sup>5</sup> Partially hydrogenated ditallow dimethyl ammonium chloride, commercially available from Sherex Chemical Company, Dublin, Ohio, USA.	
20	<sup>6</sup> Dimethyl dibehenyl/diarachidyl ammonium chloride, commercially available from Witco Chemical Corporation, Memphis, Tennessee, USA.	

The composition is prepared as follows. The Styling Agent and Premix are blended separately by conventional means. The Main Mix is prepared by adding all the ingredients and heating to 95°C for 1/2 hour with agitation. As the batch is cooled to about 60°C, the Premix and Styling Agent mixes are added to the Main Mix with agitation and the batch is cooled to ambient temperature.

#### Example VII

The following is a hair styling composition which is representative of the present invention.

30	<u>Ingredient</u>	<u>Wt. %</u>
	Premix 1:	
	G. E. SE 76 Gum <sup>1</sup>	0.80
	Cab-O-Sil HS-5 <sup>2</sup>	0.20
35	Decamethylcyclopentasiloxane	4.50



- 55 -

## Premix 2:

	G. E. SE 76 Gum	0.50
	Decamethylcyclopentasiloxane	2.80
	Natrosol Plus CS Grade D-67 <sup>1</sup>	1.39
5	Diricinoleyl dimethyl ammonium methylsulfate (DRDMAMS)	0.50
	Glydant <sup>4</sup>	0.37
	Disodium phosphate	0.12
	Monosodium phosphate	0.03
10	Disodium EDTA <sup>5</sup>	0.15
	Fragrance	0.02
	DRO H <sub>2</sub> O	q.s. to 100%
	<sup>1</sup> Polydimethylsiloxane gum offered by General Electric	
	<sup>2</sup> Fumed silica offered by the Cabot Corp.	
15	<sup>3</sup> Hydrophobically modified hydroxyethyl cellulose available from Aqualon Co.	
	<sup>4</sup> Preservative offered by Glyco, Inc.	
	<sup>5</sup> Ethylene diamine tetraacetic acid	

20 The composition is prepared as follows. The DRO water is heated to 65°F. The EDTA, phosphates, and DRDMAMS are added to the water with mixing for about 10 minutes. The Natrosol is then added with mixing for about 5 minutes. The silicone gum premixes are then added with mixing. The composition is then homogenized with a disperser, for example a Gifford-Wood Mill, for about 25 minutes. The batch is cooled to 100°F. The Glydant and perfume are added with mixing for about 10 minutes. The batch is cooled to ambient temperature and stored.

Example VIII

30 The following is a hair conditioner which is representative of the present invention.

IngredientWt. %

## Premix:

G. E. SE 76 Gum <sup>1</sup>	0.10
------------------------------	------

35

- 56 -

	Decamethylcyclopentasiloxane	0.60
	Natrosol Plus CS Grade D-67 <sup>2</sup>	1.50
	Hydrogenated tallowamide DEA	0.70
	Adogen 470 <sup>3</sup>	0.50
5	Glydant <sup>4</sup>	0.37
	Disodium EDTA <sup>5</sup>	0.15
	Disodium phosphate	0.12
	Monosodium phosphate	0.03
	Fragrance	0.02
10	DRO H <sub>2</sub> O	q.s. to 100%
	<sup>1</sup> Polydimethylsiloxane gum offered by General Electric	
	<sup>2</sup> Hydrophobically modified hydroxyethyl cellulose available from Aqualon	
	<sup>3</sup> Di partially(hydrogenated) tallow dimethyl ammonium chloride offered by Sherex Chemical Co.	
15	<sup>4</sup> Preservative offered by Glyco, Inc.	
	<sup>5</sup> Ethylene diamine tetraacetic acid	

The composition is prepared as follows. The DRO water is heated to 65°F. The EDTA, phosphates, DEA, and Adogen are added to the water with mixing for about 10 minutes. The Natrosol is then added with mixing for about 5 minutes. The silicone gum premix is then added with mixing. The composition is then homogenized with a disperser, for example a Gifford-Wood Mill, for about 2 minutes. The batch is cooled to 38°F. The Glydant and perfume are added with mixing for about 10 minutes. The batch is cooled to ambient temperature and stored.

#### Example IX

The following is a hair styling rinse composition representative of the present invention.

30	<u>Component</u>	<u>Weight %</u>
	Natrosol Plus CS Grade D-67 <sup>1</sup>	1.15
	ADOGEN 470 <sup>5</sup>	0.75
	Citric Acid	0.07
	Sodium Citrate	0.17
35	Styling Polymer Premix -	

- 57 -

	Styling Polymer <sup>2</sup>	2.5
	Phenyl Ethyl Pentamethyl Disiloxane	1.875
	Octamethyl Cyclotetrasiloxane	5.625
	Butyl Stearate	0.20
5	Silicone Gum Premix -	
	Polydimethyl Siloxane Gum <sup>3</sup>	0.35
	Decamethyl Cyclopentasiloxane	1.98
	Kathon CG	0.033
	Perfume	0.2
10	Xanthan Gum <sup>4</sup>	0.25
	DRO Water	q.s. to 100%
	<sup>1</sup> Hydrophobically modified hydroxyethyl cellulose available from Aqualon Corp.	
15	<sup>2</sup> 80/20 t-Butylacrylate/PDMS macromer, the macromer having a molecular weight of about 10,000, prepared in a manner similar to Example C-2b of U.S. Patent 4,728,571, Clemens, issued March 1, 1988	
	<sup>3</sup> S.E.-76 gum available from General Electric	
	<sup>4</sup> Readily dispersible xanthan gum	
20	<sup>5</sup> Partially hydrogenated ditallow dimethyl ammonium chloride, commercially available from Sherex Chemical Company, Dublin, Ohio, USA.	

The composition is prepared as follows.

25 The styling polymer premix is prepared by combining the styling polymer, phenyl ethyl pentamethyl disiloxane, butyl stearate, and the octamethyl cyclotetrasiloxane.

The silicone gum premix is prepared by combining, in a separate vessel and mixing the silicone gum and the decamethyl cyclopenta siloxane until homogeneous.

30 About one-half of the DRO water is first heated to about 66°C. The citric acid, and sodium citrate are added and mixed until homogeneous. The Natrosol and xanthan gum are added and mixed until homogeneous. The composition is cooled to about 38°C. The styling polymer premix, Kathon CG and perfume are added. The

35

- 58 -

composition is mixed and homogenized with a homogenizer such as a Tekmar homogenizer (preferably in-line).

The remaining DRO water is heated to about 88°C, the ADOGEN 470 is added and mixed until homogeneous. The mixture is then cooled to about 43°C. The silicone gum premix is added and the composition homogenized with a homogenizer (in-line preferred).

The two premixes are then combined and mixed until homogeneous to form the styling rinse composition.

#### Example X

The following is a hair styling rinse composition representative of the present invention.

	<u>Component</u>	<u>Weight %</u>
	Natrosol Plus CS Grade D-67 <sup>1</sup>	1.15
	ADOGEN 470 <sup>5</sup>	0.75
15	Stearyl Alcohol	0.2
	Cetyl Alcohol	0.3
	Citric Acid	0.07
	Sodium Citrate	0.17
	Styling Polymer Premix -	
20	Styling Polymer <sup>2</sup>	2.5
	Decamethyl Cyclopentasiloxane	1.875
	Octamethyl Cyclotetrasiloxane	5.625
	Silicone Gum Premix -	
	Polydimethyl Siloxane Gum <sup>3</sup>	0.35
25	Decamethyl Cyclopentasiloxane	1.98
	Kathon CG	0.033
	Perfume	0.2
	Xanthan Gum <sup>4</sup>	0.25
	DRO Water	q.s. to 100%
30	<sup>1</sup> Hydrophobically modified hydroxyethyl cellulose available from Aqualon Corp.	
	<sup>2</sup> 80/20 t-Butylacrylate/PDMS macromer, the macromer having a molecular weight of about 10,000, prepared in a manner similar to Example C-2b of U.S. Patent 4,728,571, Clemens, issued March 1, 1988	
35		

- 59 -

- 3 S.E.-76 gum available from General Electric
- 4 Readily dispersible xanthan gum
- 5 Partially hydrogenated ditallow dimethyl ammonium chloride,  
commercially available from Sherex Chemical Company, Dublin,  
Ohio, USA.

The composition is prepared as follows.

The styling polymer premix is prepared by combining the styling polymer, decamethyl cyclopentasiloxane, and the octamethyl cyclotetrasiloxane.

- 10 The silicone gum premix is prepared by combining, in a separate vessel and mixing the silicone gum and the decamethyl cyclopenta siloxane until homogeneous.

- 15 About one-half of the DRO water is first heated to about 66°C. The citric acid, and sodium citrate are added and mixed until homogeneous. The Natrosol and xanthan gum are added and mixed until homogeneous. The composition is cooled to about 38°C. The styling polymer premix, Kathon CG and perfume are added. The composition is mixed and homogenized with a homogenizer such as a Tekmar homogenizer (preferably in-line).

- 20 The remaining DRO water is heated to about 88°C, the ADOGEN 470 stearyl alcohol and cetyl alcohol are added and mixed until homogeneous. The mixture is then cooled to about 43°C. The silicone gum premix is added and the composition homogenized with a homogenizer (in-line preferred).

- 25 The two premixes are then combined and mixed until homogeneous to form the styling rinse composition.

#### Example XI

The following is a hair styling rinse composition representative of the present invention.

30	<u>Component</u>	<u>Weight %</u>
	Natrosol Plus CS Grade D-67 <sup>1</sup>	1.15
	ADOGEN 470 <sup>5</sup>	0.75
	Citric Acid	0.07
	Sodium Citrate	0.17
35	Styling Polymer Premix -	

- 60 -

	Styling Polymer <sup>2</sup>	2.5
	Phenyl Ethyl Pentamethyl Disiloxane	1.875
	Octamethyl Cyclotetrasiloxane	5.625
	Silicone Gum/Fluid Premix	
5	Polydimethyl Siloxane Gum <sup>3</sup>	0.20
	350 centistoke Polydimethyl Siloxane Fluid	0.30
	Kathon CG	0.033
	Perfume	0.2
	Xanthan Gum <sup>4</sup>	0.25
10	DRO Water	q.s. to 100%
	<sup>1</sup> Hydrophobically modified hydroxyethyl cellulose available from Aqualon Corp.	
	<sup>2</sup> 80/20 t-Butylacrylate/PDMS macromer, the macromer having a molecular weight of about 10,000, prepared in a manner similar to Example C-2b of U.S. Patent 4,728,571, Clemens, issued March 1, 1988	
15	<sup>3</sup> S.E.-76 gum available from General Electric	
	<sup>4</sup> Readily dispersible xanthan gum	
	<sup>5</sup> Partially hydrogenated ditallow dimethyl ammonium chloride, commercially available from Sherex Chemical Company, Dublin, Ohio, USA.	
20		

The composition is prepared as follows.

The styling polymer premix is prepared by combining the styling polymer, phenyl ethyl pentamethyl disiloxane, and the octamethyl cyclotetrasiloxane.

The silicone gum/fluid premix is prepared by combining in a separate vessel and mixing the silicone gum and silicone fluid until homogeneous.

About one-half of the DRO water is first heated to about 66°C. The citric acid, and sodium citrate are added and mixed until homogeneous. The Natrosol and xanthan gum are added and mixed until homogeneous. The composition is cooled to about 38°C. The styling polymer premix, Kathon CG and perfume are added. The composition is mixed and homogenized with a homogenizer such as a Tekmar homogenizer (preferably in-line).

- 61 -

The remaining DRO water is heated to about 88°C, the ADOGEN 470 is added and mixed until homogeneous. The mixture is then cooled to about 43°C. The silicone gum/fluid premix is added and the composition homogenized with a homogenizer (in-line preferred).

The two premixes are then combined and mixed until homogeneous to form the styling rinse composition.

#### Example XII

The following is a hair styling rinse composition representative of the present invention.

	<u>Component</u>	<u>Weight %</u>
	Natrosol Plus CS Grade D-67 <sup>1</sup>	1.15
	Hydrogenated Tallow Betaine	0.30
	Methyl-1-soya amido ethyl-2-soya	0.75
15	imidazolinium (MSAESI)	
	Citric Acid	0.07
	Sodium Citrate	0.17
	Styling Polymer Premix -	
	Styling Polymer <sup>2</sup>	2.5
20	Octamethyl Cyclotetrasiloxane	5.25
	Decamethyl Cyclopentasiloxane	2.25
	Silicone Gum Premix -	
	Polydimethyl Siloxane Gum <sup>3</sup>	0.35
	Decamethyl Cyclopentasiloxane	1.98
25	Kathon CG	0.033
	Perfume	0.2
	Xanthan Gum <sup>4</sup>	0.25
	DRO Water	q.s. to 100%
30	<sup>1</sup> Hydrophobically modified hydroxyethyl cellulose available from Aqualon Corp.	
	<sup>2</sup> 80/20 t-Butylacrylate/PDMS macromer, the macromer having a molecular weight of about 10,000, prepared in a manner similar to Example C-2b of U.S. Patent 4,728,571, Clemens, issued March 1, 1988	
35	<sup>3</sup> S.E.-76 gum available from General Electric	

- 62 -

4 Readily dispersible xanthan gum

The composition is prepared as follows.

The styling polymer premix is prepared by combining the styling polymer, the octamethyl tetrasiloxane, and the decamethyl pentasiloxane.

The silicone gum premix is prepared by combining, in a separate vessel and mixing the silicone gum and the decamethyl cyclopentasiloxane until homogeneous.

About one-half of the DRO water is first heated to about 66°C. The hydrogenated tallow betaine, citric acid, and sodium citrate are added and mixed until homogeneous. The Natrosol and xanthan gum are added and mixed until homogeneous. The composition is cooled to about 38°C. The styling polymer premix, Kathon CG and perfume are added. The composition is mixed and homogenized with a homogenizer such as a Tekmar homogenizer (preferably in-line).

The remaining DRO water is heated to about 88°C, the MSAESI is added and mixed until homogeneous. The mixture is then cooled to about 43°C. The silicone gum premix is added and the composition homogenized with a homogenizer (in-line preferred).

The two premixes are then combined and mixed until homogeneous to form the styling rinse composition.

Examples XIII-XVI

The following are hair styling/conditioning rinse compositions representative of the present invention.

<u>Composition</u>	<u>XIII</u>	<u>XIV</u>	<u>XV</u>	<u>XVI</u>
Citric Acid	0.02	0.02	0.02	0.02
Sodium Citrate	0.09	0.09	0.09	0.09
Cetyl Alcohol	0.12	0.12	0.12	0.12
Stearyl Alcohol	0.08	0.08	0.08	0.08
Natrosol Plus CS Grade D-67 <sup>1</sup>	1.25	1.40	0.95	1.10
Xanthan Gum <sup>2</sup>	0.25	0.25	0.25	0.25
Styling Polymer Premix				
Styling Polymer <sup>3</sup>	1.75	1.75	1.75	1.75
Octamethyl Tetrasiloxane	5.98	5.98	5.98	5.98



- 63 -

	Decamethyl Pentasiloxane	2.56	2.56	2.56	2.56
	Butyl Stearate	0.15	0.15	0.15	0.15
	Kathon CG	0.03	0.03	0.03	0.03
	Perfume	0.33	0.33	0.33	0.33
5	Thickener Premix				
	DRO Water	11.67	11.90	11.93	11.63
	Adogen 470 <sup>5</sup>	0.67	1.33	1.00	1.00
	Kemamine® BQ-2802C	0.33	--	--	--
	Stearyl trimethyl	--	--	0.30	--
10	ammonium chloride				
	Adogen 471 <sup>6</sup>	--	--	--	0.60
	Silicone Gum Premix				
	Decamethyl Pentasiloxane	1.98	1.42	1.42	1.42
	Polydimethyl Siloxane Gum <sup>4</sup>	0.35	0.25	0.25	0.25
15	Amodimethicone (Dow Corning Q2-8220)	--	0.10	0.10	0.10
	DRO Water	q.s.	q.s.	q.s.	q.s.

<sup>1</sup>Hydrophobically modified hydroxyethyl cellulose from Aqualon Corp.

20 <sup>2</sup>Readily dispersible xantham gum

<sup>3</sup>80/20 t-Butylacrylate/PDMS macromer, the macromer having a molecular weight of about 10,000, prepared in a manner similar to Example C-2b of U.S. Patent 4,728,571, Clemens, issued March 1, 1988.

25 <sup>4</sup>SE-76 gum available From General Electric

<sup>5</sup>Solution of 75% surfactant and 25% isopropyl alcohol/water for Examples XV and XVI; 100% surfactant for Examples XIII and XIV.

<sup>6</sup>Tallow trimethyl ammonium chloride (Sherex Chemical Co.)

30 The styling polymer premix is prepared by combining the styling polymer, the octamethyl tetrasiloxane and decamethyl pentasiloxane, and butyl stearate.

The silicone gum premix is prepared by combining and mixing (in a separate vessel) the silicone gum and decamethyl pentasiloxane until homogeneous.

35

- 64 -

The thickener premix is prepared by combining and mixing (in a separate vessel) DRO water, and any primary and secondary thickeners (premelted if necessary to ensure homogeneity) at 82°C, and the silicone gum premix and the amodimethicone at 71°C, until homogeneous.

In another vessel, the DRO water is heated to 71°C. Citric acid, sodium citrate, cetyl alcohol, stearyl alcohol and Natrosol Plus CS grade D-67 are added and mixed until homogeneous. The xanthan gum is added and mixed until homogeneous. The styling polymer premix, Kathon CG and perfume are added and mixed until homogeneous. The composition is further dispersed with an in-line homogenizer (such as Tekmar homogenizer) and then cooled to 38°C.

The thickener premix is also further dispersed with an in-line homogenizer and cooled to 38°C and added to the final vessel, mixing until homogeneous to form the styling rinse composition.

The compositions hereof comprise or, alternatively, can consist essentially of or consist of the essential ingredients, as well as the various optional ingredients, described herein.

WHAT IS CLAIMED IS:

65


## Claims:

1. A cosmetic composition useful for application to the hair or skin, characterized in that it comprises:


(a) from 80% to 100% of a vehicle system which comprises:

(A) from 0.1% to 10.0% by weight of the cosmetic composition of a hydrophobically modified nonionic water-soluble polymer which comprises a water-soluble polymer backbone and hydrophobic groups selected from the group consisting of  $C_4$ - $C_{22}$  alkyl, aryl alkyl, alkyl aryl groups and mixtures thereof; wherein the ratio of the hydrophilic portion to the hydrophobic portion of the polymer is from 10:1 to 1000:1; and

(B) from 0.02% to 10.0%, preferably 0.05% to 3.0%, by weight of the cosmetic composition of unsaturated quaternary ammonium surfactant component of the formula:




wherein X is a salt-forming anion, a is the ionic charge of X, the quaternary ammonium radicals  $R_1$ ,  $R_2$ ,  $R_3$ , and  $R_4$  independently are  $C_1$  -  $C_{22}$  alkyl,  $C_{14}$  -  $C_{22}$  alkyl amido  $C_2$  -  $C_6$  alkylene, or benzyl, and from two to three of said quaternary ammonium radicals, are  $C_{14}$ - $C_{22}$  alkyl or  $C_{14}$ - $C_{22}$  alkyl amido  $C_2$ - $C_6$  alkylene or mixtures thereof, no more than two of said radicals being  $C_{14}$ - $C_{22}$  alkyl amido  $C_2$ - $C_6$  alkylene or a combination of  $C_{14}$ - $C_{22}$  alkyl and  $C_{14}$ - $C_{22}$  alkyl amido  $C_2$ - $C_6$  alkylene, from one to two of said quaternary ammonium radicals are  $C_1$ - $C_6$  alkyls, and no more than one of said radicals is benzyl; or



wherein X is a salt-forming anion, a is the ionic charge of X, radicals  $R_1$ ,  $R_2$ , and  $R_3$  independently are  $C_1$ - $C_{22}$  alkyl or benzyl, and two or three of said radicals are  $C_{14}$ - $C_{22}$  alkyl, or  $C_{14}$ - $C_{22}$  alkyl amido  $C_2$ - $C_6$  alkylene or a mixture thereof, zero or one of said radicals are  $C_1$ - $C_6$  alkyl, zero or one of said radicals is benzyl, or a mixture of Formula I and II surfactants; wherein said the quaternary ammonium surfactant component has a sufficient level of unsaturation in the  $C_{14}$ - $C_{22}$  alkyl or  $C_{14}$ - $C_{22}$  alkyl amido  $C_2$ - $C_6$  alkylene radicals, or mixture thereof, such that average iodine value of said component is at least 15; and

- (C) from 65% to 99% by weight of the cosmetic composition of a compatible solvent; and
- (b) from 0% to 20% of an additional cosmetic component; wherein said cosmetic compositions comprise no more than 1.0% of water-soluble surfactants.

2. A hair care composition according to Claim 1 comprising a cationic quaternary ammonium surfactant of the formula:



wherein X is a salt-forming anion, a is the charge of X, the radicals  $R_1$ ,  $R_2$ ,  $R_3$ , and  $R_4$  independently are  $C_1$ - $C_6$  alkyl,  $C_{20}$ - $C_{22}$  alkyl, or benzyl wherein one of said radicals is  $C_{20}$ - $C_{22}$  alkyl, preferably  $C_{22}$ , from two to three of said


radicals are  $C_1$ - $C_6$  alkyl, and zero or one of said radicals is benzyl; wherein, preferably the weight ratio of the total of the surfactants of Formula I and Formula II to Formula III is from 1:1 to 4:1.

3. A hair styling and conditioning composition comprising:

(a) from 80% to 99.8% of a vehicle system which comprises:


(A) from 0.1% to 10.0% by weight of the cosmetic composition of a hydrophobically modified nonionic water-soluble polymer which comprises a water-soluble polymer backbone and hydrophobic groups selected from the group consisting of  $C_8$ - $C_{22}$  alkyl, aryl alkyl, alkyl aryl groups and mixtures thereof; wherein the ratio of the hydrophilic portion to the hydrophobic portion of the polymer is from 10:1 to 1000:1; and

(B) from 0.02% to 10.0%, preferably 0.05% to 3.0%, by weight of the cosmetic composition of unsaturated quaternary ammonium surfactant component of the formula:




wherein X is a salt-forming anion, a is the ionic charge of X, the quaternary ammonium radicals  $R_1$ ,  $R_2$ ,  $R_3$ , and  $R_4$  independently are  $C_1$  -  $C_{22}$  alkyl,  $C_{14}$  -  $C_{22}$  alkyl amido  $C_2$  -  $C_6$  alkylene, or benzyl, and from two to three of said quaternary ammonium radicals, are  $C_{14}$ - $C_{22}$  alkyl or  $C_{14}$ - $C_{22}$  alkyl amido  $C_2$ - $C_6$  alkylene or mixtures thereof, no more than two of said radicals being  $C_{14}$ - $C_{22}$  alkyl amido  $C_2$ - $C_6$  alkylene or a combination of  $C_{14}$ - $C_{22}$  alkyl and  $C_{14}$ - $C_{22}$  alkyl amido  $C_2$ - $C_6$  alkylene, from one to two of said quaternary ammonium radicals are

C<sub>1</sub>-C<sub>6</sub> alkyls, and no more than one of said radicals is benzyl; or



wherein X is a salt-forming anion, a is the ionic charge of X, radicals R<sub>1</sub>, R<sub>2</sub>, and R<sub>3</sub> independently are C<sub>1</sub>-C<sub>22</sub> alkyl or benzyl, and two or three of said radicals are C<sub>14</sub>-C<sub>22</sub> alkyl, or C<sub>14</sub>-C<sub>22</sub> alkyl amido C<sub>2</sub>-C<sub>6</sub> alkylene or a mixture thereof, zero or one of said radicals are C<sub>1</sub>-C<sub>6</sub> alkyl, zero or one of said radicals is benzyl, or a mixture of Formula I and II surfactants; wherein said the quaternary ammonium surfactant component has a sufficient level of unsaturation in the C<sub>14</sub>-C<sub>22</sub> alkyl or C<sub>14</sub>-C<sub>22</sub> alkyl amido C<sub>2</sub>-C<sub>6</sub> alkylene radicals, or mixture thereof, such that average iodine value of said component is at least 15; and

- (C) from 65% to 99% by weight of the cosmetic composition of a compatible diluent; and
- (b) from 0.1% to 10%, by weight of the composition, of a hair setting agent;
- (c) from 0.01% to 5% of a distributing aid; and
- (d) from 0.05% to 1.0%, by weight of the composition, of a mono-long chain, tri-short chain quaternary ammonium surfactant of the formula:



wherein X is a salt forming anion,  $z$  is the ionic charge of X, the quaternary ammonium radical  $R_1$  is  $C_{14}-C_{22}$  alkyl or  $C_{14}-C_{22}$  alkyl amido  $C_2-C_6$  alkylene and quaternary ammonium radicals  $R_2$ ,  $R_3$ , and  $R_4$  independently are  $C_1-C_6$  alkyl or benzyl, wherein zero or one of said  $R_2$ ,  $R_3$ , and  $R_4$  radicals is benzyl;

wherein said composition comprises no more than 1.0% of water-soluble surfactants.

4. A composition comprising a hair setting agent as in Claim 3, wherein said hair setting agent comprises a water-insoluble styling polymer solubilized or dispersed in a water-insoluble solvent.

5. A composition, as in Claim 4, wherein said hair styling polymer is a silicone-containing polymer.

6. A composition, as in Claim 4 or 5, wherein said solvent of said hair setting agent is a volatile silicone fluid.

7. A hair care composition according to Claim 1, 2, 3, 4, 5, or 6 which comprises from 0.1% to 10% by weight of said composition, of a hair setting agent which comprises a copolymer which has a vinyl polymeric backbone having grafted to it monovalent siloxane polymeric moieties, said copolymer comprising C monomers and components selected from the group consisting of A monomers, B monomers, and mixtures thereof, wherein:

A is at least one free radically polymerizable monomer, the amount by weight of A monomer, when used, being up to 98% by weight of the total weight of all monomers in said copolymer;

B is at least one monomer copolymerizable with A, the amount by weight of B monomer, when used, being up to 98% of the total weight of all monomers in said copolymer, said B monomer being selected from monomers that are polar relative to A; and

C is a polymeric monomer having a molecular weight of from 1,000 to 50,000 and the general formula

$X(Y)_nSi(R)_{3-m}(Z)_m$  wherein

X is a vinyl group copolymerizable with the A and B monomers

Y is a divalent linking group

R is a hydrogen, lower alkyl, aryl or alkoxy

Z is a monovalent siloxane polymeric moiety having a number average molecular weight of at least 500, is essentially unreactive under copolymerization conditions, and is pendant from said vinyl polymeric backbone after polymerization

n is 0 or 1

m is an integer from 1 to 3

wherein C comprises from 0.01% to 50% of the copolymer;

wherein preferably the copolymer comprises from 5% to 98% A monomer, from 0.1% to 50% C monomer, and from 0% to 98% B monomer.

8. A hair care composition according to Claim 7 wherein monomer A is selected from the group consisting of acrylic acid esters of  $C_1$ - $C_{18}$  alcohols, methacrylic acid esters of  $C_1$ - $C_{18}$  alcohols, styrene, vinyl acetate, vinyl chloride, vinylidene chloride, acrylonitrile, alpha-methylstyrene, t-butylstyrene, butadiene, cyclohexadiene, ethylene, propylene, vinyl toluene, polystyrene macromer, and mixtures thereof, preferably A is selected from the group consisting of n-butylmethacrylate, isobutylmethacrylate, 2-ethylhexyl methacrylate, t-butylacrylate, t-butylmethacrylate, methylmethacrylate, and mixtures thereof, and monomer B is selected from the group consisting of acrylic acid, methacrylic acid, N,N-dimethylacrylamide, dimethylaminoethyl methacrylate, quaternized dimethylaminoethyl methacrylate, methacrylonitrile, methacryloamide, maleic anhydride, half esters of maleic anhydride, itaconic acid, acrylamide, acrylate alcohols, hydroxyethyl methacrylate, diallyldimethyl ammonium chloride, vinyl pyrrolidone, vinyl ethers, maleimides, vinyl pyridine, vinyl imidazole, styrene sulfonate, and mixtures thereof.



9. The composition of Claim 1, 2, 3, 4, 5, 6, 7, 8, or 9 wherein said radicals of Formula I are selected from the group consisting of C<sub>14</sub>-C<sub>22</sub> alkyl, C<sub>1</sub>-C<sub>6</sub> alkyl, benzyl, and C<sub>14</sub>-C<sub>22</sub> alkyl amido C<sub>2</sub>-C<sub>6</sub> alkylene, and said radicals of Formula II are selected from the group consisting of C<sub>14</sub>-C<sub>22</sub> alkyl, C<sub>1</sub>-C<sub>6</sub> alkyl, benzyl, and C<sub>14</sub>-C<sub>22</sub> alkyl amido C<sub>2</sub>-C<sub>6</sub> alkylene, and preferably, the cationic quaternary ammonium surfactant is selected from the group consisting of compounds of Formula I wherein two of said radicals are C<sub>16</sub>-C<sub>22</sub> alkyl, from one to two of said radicals are C<sub>1</sub>-C<sub>6</sub> alkyl, and zero or one of said radicals is benzyl, and compounds of Formula II wherein two of said radicals are C<sub>16</sub>-C<sub>22</sub> alkyl, and one of said radicals is C<sub>1</sub>-C<sub>6</sub> alkyl or benzyl.

10. The composition of Claim 1, 2, 3, 4, 5, 6, 7, 8, or 9 wherein said cationic quaternary ammonium surfactant comprises: salts of dimethyl di(unsaturated) tallow ammonium, dimethyl di(unsaturated)arachidyl ammonium, dioleyl dimethylammonium, di-rapeseed alkyl dimethyl ammonium, diricinoleyl dimethyl ammonium, and disoyadimonium, olealkonium, methyl-1-oleyl amido ethyl-2-oleyl imidazolinium, dierucyl dimethyl ammonium, and methyl-1-soya amido ethyl-2-soya imidazolinium.

11 The composition of Claim 1, 2, 3, 4, 5, 6, 7, 8, 9, or 10 wherein said hydrophobically modified nonionic water-soluble polymer comprises a nonionic cellulose ether, preferably a long-chain alkyl radical attached via an ether linkage, having a sufficient degree of nonionic substitution, selected from the group consisting of methyl, hydroxyethyl, and hydroxypropyl, to cause it to be water-soluble and being further substituted with a long chain alkyl radical having 10 to 24 carbon atoms in an amount between 0.2 weight percent and the amount which renders said cellulose ether less than 0.2% by weight soluble in water, preferably less than 1.0% by weight soluble in water, and also preferably, the vehicle system provides a rheology to the cosmetic composition that is characterized by a shear stress of from 0 to

50 pascal over a shear rate range of from  $0.04 \text{ sec}^{-1}$  to  $25 \text{ sec}^{-1}$ , and most preferably the water-soluble hydroxyethyl cellulose is substituted with a long chain alkyl radical having 16 carbon atoms in an amount between 0.40% to 0.95%, by weight; the hydroxyethyl molar substitution is from 2.3 to 3.7; and the average molecular weight of the unsubstituted cellulose is from 300,000 to 700,000.


12. The composition of Claim 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, or 11 wherein the composition comprises no more than 1% of fatty alcohol materials.

13. The cosmetic composition of Claim 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, or 12 which is a hair care composition comprising at least 0.1% of an additional active cosmetic compositions and wherein said additional active cosmetic component comprises a hair conditioning component selected from the group consisting of a volatile silicone fluid having a viscosity of less than 10 centipoise at  $25^{\circ}\text{C}$ ; a non-volatile silicone fluid having a viscosity of less than 100,000 centipoise at  $25^{\circ}\text{C}$ ; a silicone gum having a viscosity greater than 1,000,000 centipoise at  $25^{\circ}\text{C}$ ; and mixtures thereof.

## INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 92/00805

<b>I. CLASSIFICATION OF SUBJECT MATTER</b> (if several classification symbols apply, indicate all) <sup>6</sup>		
According to International Patent Classification (IPC) or to both National Classification and IPC Int.Cl. 5 A61K7/06; A61K7/08; A61K7/48		
<b>II. FIELDS SEARCHED</b>		
Minimum Documentation Searched <sup>7</sup>		
Classification System	Classification Symbols	
Int.Cl. 5	A61K	
Documentation Searched other than Minimum Documentation to the extent that such Documents are Included in the Fields Searched <sup>8</sup>		
<b>III. DOCUMENTS CONSIDERED TO BE RELEVANT<sup>9</sup></b>		
Category <sup>10</sup>	Citation of Document, <sup>11</sup> with indication, where appropriate, of the relevant passages <sup>12</sup>	Relevant to Claim No. <sup>13</sup>
X	EP,A,0 412 710 (THE PROCTER & GAMBLE COMPANY) 13 February 1991 see the whole document ---	1-9, 11-13
X	EP,A,0 412 706 (THE PROCTER & GAMBLE COMPANY) 13 February 1991 see the whole document ---	1-9, 11-13
X	EP,A,0 412 705 (THE PROCTER & GAMBLE COMPANY) 13 February 1991 see the whole document ---	1,7,8,11
P,X	WO,A,9 116 878 (THE PROCTER & GAMBLE COMPANY) 14 November 1991 see the whole document ---	1,2,7-9, 11,12
-/-		
<p><sup>10</sup> Special categories of cited documents : <sup>10</sup></p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step</p> <p>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.</p> <p>"&amp;" document member of the same patent family</p>		
<b>IV. CERTIFICATION</b>		
Date of the Actual Completion of the International Search	Date of Mailing of this International Search Report	
04 AUGUST 1992	13. 08. 92	
International Searching Authority	Signature of Authorized Officer	
EUROPEAN PATENT OFFICE	COUCKUYT P.J.R. 	

III. DOCUMENTS CONSIDERED TO BE RELEVANT (CONTINUED FROM THE SECOND SHEET)		
Category	Citation of Document, with indication, where appropriate, of the relevant passages	Relevant to Claim No.
P,A	EP,A,0 467 235 (HELENE CURTIS INC.) 22 January 1992 see the whole document ---	1-13

ANNEX THE INTERNATIONAL SEARCH REPORT  
ON INTERNATIONAL PATENT APPLICATION NO.

US 9200805  
SA 58711

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report.  
The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information. 04/08/92

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP-A-0412710	13-02-91	US-A- 5106609	21-04-92
		AU-A- 6015990	07-02-91
		JP-A- 3218306	25-09-91
		CN-A- 1056051	13-11-91
EP-A-0412706	13-02-91	US-A- 5104646	14-04-92
		AU-A- 6016090	07-02-91
		CA-A- 2022469	08-02-91
		CN-A- 1049969	20-03-91
		JP-A- 3141214	17-06-91
EP-A-0412705	13-02-91	US-A- 5100658	31-03-92
		AU-A- 6016190	07-02-91
		CA-A- 2022468	08-02-91
		CN-A- 1049785	13-03-91
		JP-A- 3141210	17-06-91
WO-A-9116878	14-11-91	US-A- 5100657	31-03-92
		AU-A- 7852091	27-11-91
		CN-A- 1056050	13-11-91
EP-A-0467235	22-01-92	US-A- 5078990	07-01-92
		AU-A- 8040591	16-01-92
		CA-A- 2046934	14-01-92

EPO FORM P0079

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82





INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification <sup>5</sup> :  A61K 7/06, 7/08, 7/48</p>	<p>A1</p>	<p>(11) International Publication Number: <b>WO 92/16187</b>  (43) International Publication Date: 1 October 1992 (01.10.92)</p>
<p>(21) International Application Number: PCT/US92/00805 (22) International Filing Date: 31 January 1992 (31.01.92) (30) Priority data: 671,576 19 March 1991 (19.03.91) US 776,960 15 October 1991 (15.10.91) US (71) Applicant: THE PROCTER &amp; GAMBLE COMPANY [US/US]; One Procter &amp; Gamble Plaza, Cincinnati, OH 45202 (US). (72) Inventors: COFFINDAFFER, Timothy, Woodrow ; 118 Bridle Lane, Loveland, OH 45140 (US). MONICH, Me- lissa, Smith ; 10574 Latina Ct., Cincinnati, OH 45218 (US). LEITCH, Steven, Hilary ; 2840-E Macintosh Lane, Maineville, OH 45039 (US). McCALL, Patrick, Colum- kille ; 10736 Bridle Path Lane, Cincinnati, OH 45215 (US).</p>		<p>(74) Agent: REED, T., David; The Procter &amp; Gamble Com- pany, Ivorydale Technical Ctr., 5299 Spring Grove Ave., Cincinnati, OH 45217-1087 (US). (81) Designated States: AT, AT (European patent), AU, BB, BE (European patent), BF (OAPI patent), BG, BJ (OAPI patent), BR, CA, CF (OAPI patent), CG (OAPI patent), CH, CH (European patent), CI (OAPI patent), CM (OAPI patent), CS, DE, DE (European patent), DK, DK (European patent), ES, ES (European patent), FI, FR (European patent), GA (OAPI patent), GB, GB (Eu- ropean patent), GN (OAPI patent), GR (European pa- tent), HU, IT (European patent), JP, KP, KR, LK, LU, LU (European patent), MC (European patent), MG, ML (OAPI patent), MN, MR (OAPI patent), MW, NL, NL (European patent), NO, PL, RO, RU, SD, SE, SE (Euro- pean patent), SN (OAPI patent), TD (OAPI patent), TG (OAPI patent).  <b>Published</b> <i>With a revised version of the international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>  (88) Date of publication of the revised version of the international search report: 10 December 1992 (10.12.92)</p>
<p>(54) Title: COSMETIC COMPOSITIONS CONTAINING HYDROPHOBICALLY MODIFIED NONIONIC POLYMER AND UNSATURATED QUATERNARY AMMONIUM SURFACTANT</p>		
<p>(57) Abstract</p> <p>Disclosed is a vehicle system having a thickening system which comprises a nonionic long-chain alkylated water-soluble polymer and a specific cationic quaternary ammonium surfactant component dispersed in a compatible solvent. The quaternary surfactant component has an iodine value of at least about 15. The quaternary surfactant component is characterized by having a sufficient level of unsaturated C<sub>14</sub>-C<sub>22</sub> alkyl or C<sub>14</sub>-C<sub>22</sub> alkyl amido C<sub>2</sub>-C<sub>6</sub> alkylene radicals such that the average iodine value is at least about 15. These vehicle systems are useful in cosmetic compositions which are used to deliver an active component to the hair or skin. The vehicle systems are particularly useful in hair care compositions, especially rinse-off hair conditioning and styling compositions. In a particular rinse-off hair styling and conditioning composition hereof, the composition contains a vehicle system, as described above, and additionally contains a hair setting agent, a distributing aid, and a mono-long chain, tri-short chain quaternary ammonium surfactant.</p>		

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FI	Finland	MI	Mali
AU	Australia	FR	France	MN	Mongolia
BB	Barbados	GA	Gabon	MR	Mauritania
BE	Belgium	GB	United Kingdom	MW	Malawi
BF	Burkina Faso	GN	Guinea	NL	Netherlands
BG	Bulgaria	GR	Greece	NO	Norway
BJ	Benin	HU	Hungary	PL	Poland
BR	Brazil	IE	Ireland	RO	Romania
CA	Canada	IT	Italy	RU	Russian Federation
CF	Central African Republic	JP	Japan	SD	Sudan
CG	Congo	KP	Democratic People's Republic of Korea	SE	Sweden
CH	Switzerland	KR	Republic of Korea	SN	Senegal
CI	Côte d'Ivoire	LI	Liechtenstein	SU	Soviet Union
CM	Cameroon	LK	Sri Lanka	TD	Chad
CS	Czechoslovakia	LU	Luxembourg	TG	Togo
DE	Germany	MC	Monaco	US	United States of America
DK	Denmark	MG	Madagascar		
ES	Spain				



REVISED  
VERSION

INTERNATIONAL SEARCH REPORT

International Application No.

PCT/US 92/00805

I. CLASSIFICATION OF SUBJECT MATTER (If several classification symbols apply, indicate all)<sup>6</sup>

According to International Patent Classification (IPC) or to both National Classification and IPC

Int.Cl. 5 A61K7/06; A61K7/08; A61K7/48

II. FIELDS SEARCHED

Minimum Documentation Searched<sup>7</sup>

Classification System	Classification Symbols
Int.Cl. 5	A61K

Documentation Searched other than Minimum Documentation  
to the extent that such Documents are included in the Fields Searched<sup>8</sup>

III. DOCUMENTS CONSIDERED TO BE RELEVANT<sup>9</sup>

Category <sup>*</sup>	Citation of Document, <sup>11</sup> with indication, where appropriate, of the relevant passages <sup>12</sup>	Relevant to Claim No. <sup>13</sup>
X	EP,A,0 412 710 (THE PROCTER & GAMBLE COMPANY) 13 February 1991 see the whole document ---	1-9, 11-13
X	EP,A,0 412 706 (THE PROCTER & GAMBLE COMPANY) 13 February 1991 see the whole document ---	1-9, 11-13
X	EP,A,0 412 705 (THE PROCTER & GAMBLE COMPANY) 13 February 1991 see the whole document ---	1,7,8,11
P,X	WO,A,9 115 186 (THE PROCTER & GAMBLE COMPANY) 17 October 1991 see the whole document ---	1,2,7-9, 11,12
	-/--	

\* Special categories of cited documents :<sup>10</sup>

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"A" document member of the same patent family

IV. CERTIFICATION

Date of the Actual Completion of the International Search

01 OCTOBER 1992

Date of Mailing of this International Search Report


09. 11. 92

International Searching Authority

EUROPEAN PATENT OFFICE

Signature of Authorized Officer

COUCKUYT P.J.R.



## III. DOCUMENTS CONSIDERED TO BE RELEVANT (CONTINUED FROM THE SECOND SHEET)

Category *	Citation of Document, with indication, where appropriate, of the relevant passages	Relevant to Claim No.
P,A	EP,A,0 467 235 (HELENE CURTIS INC.) 22 January 1992 see the whole document -----	1-13

# ANNEX TO THE INTERNATIONAL SEARCH REPORT ON INTERNATIONAL PATENT APPLICATION NO.

US 9200805  
SA 58711

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information. 01/10/92

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP-A-0412710	13-02-91	US-A- 5106609	21-04-92
		AU-A- 6015990	07-02-91
		JP-A- 3218306	25-09-91
		CN-A- 1056051	13-11-91
EP-A-0412706	13-02-91	US-A- 5104646	14-04-92
		AU-A- 6016090	07-02-91
		CA-A- 2022469	08-02-91
		CN-A- 1049969	20-03-91
		JP-A- 3141214	17-06-91
EP-A-0412705	13-02-91	US-A- 5100658	31-03-92
		AU-A- 6016190	07-02-91
		CA-A- 2022468	08-02-91
		CN-A- 1049785	13-03-91
		JP-A- 3141210	17-06-91
WO-A-9115186	17-10-91	US-A- 5120531	09-06-92
		AU-A- 7674291	30-10-91
		CN-A- 1056053	13-11-91
EP-A-0467235	22-01-92	US-A- 5078990	07-01-92
		AU-A- 8040591	16-01-92
		CA-A- 2046934	14-01-92

EPO FORM P007

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**THIS PAGE BLANK (USPTO)**